


HELIOS SLIM-LINE DOWNLIGHT

H65-15-180TC

QVIS[®]

LIGHTING & SECURITY



OSRAM


Driver as Standard




LED's inside

Specification	Helios 180
System Power	15W
Driver Manufacturer	Osram
LED Chipset	Samsung
Diffuser	Opal
Colour Rendering Index	>85
Typical UGR	<19
LED Efficacy	115 Lm/cW
Lumen Output	1725Lm
Fire Rating	TP(a)
Dimmable	Contact Office
Power Factor	0.9
IP Rating	IP65
Beam Spread	90°
Colour Type	CCT Switchable
Colour Temperature	3000K/4000K/6000K
Housing Material	High Grade 6063 Aluminium
Cut Out	160mm
Operating Temperature	-20 to 50 °C
Input Voltage	AC 200-240V, 50-60Hz
Weight	0.5kg
Dimensions	180mm x 27mm
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN 60598 2-2, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

TECHNICAL DRAWINGS



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



* Warranty terms and conditions apply

For further information on our products or terms and conditions visit our website www.qvisled.com or email: sales@qvislighting.com

MODULAR & RECESSED RANGE