

95543

Saxby HeroPRO CCT Corridor

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt white textured & opal PC finish
- Constructed from polycarbonate
- Complete with built in step dim microwave sensor
- IP65
- IK10
- Fast fit hinged gear tray
- Interchangeable bezels

SPEC DATA

| | |
|-----------------------------|------------------------|
| Product Wattage: | 9/14/18W |
| Product Lumen: | 900/1400/1800Lm |
| Lumen/W: | 100 |
| Kelvin: | 3000/4000/6000K |
| Energy Rating: | D |
| Dimmable: | No |
| Beam Angle: | 120° |
| Power Factor: | > 0.9 |
| CRI: | > 80 |
| Lifetime (Hours): | 35000 |
| LED Brand: | Epistar |
| SDCM: | < 6 |
| Driver Type: | Constant Current 180mA |
| Inrush Current at Start Up: | ≤ 10A |
| Product Voltage: | 220-240V |
| Hertz: | 50/60 |
| Surge Protection (KV): | 1.5 |
| Operating Temp.: | -20 to 45 Degree |
| Product Weight (KG): | 0.82 |
| Terminal Block: | 4-way fast fix |
| Class: | 2 |

Step Dim Microwave Movement Sensor

| | |
|------------------------|--------------------------|
| DC Input Voltage: | 12±1V DC |
| Rated Voltage: | 12±0.6V DC |
| Stand-by Power: | < 0.3W |
| Efficiency: | ≥ 80% |
| Operating Frequency: | 5.8 GHz ± 75 MHz |
| Transmitting Power: | 0.2mW Max. |
| Hold Time: | 5s / 90s / 3min / 10min |
| Stand-by DIM Level: | 10%, 30%, |
| Stand-by Period: | 0s / 30s / 10min / +∞ |
| Detection Area: | 100% / 50% |
| Daylight Sensor: | 10Lux / Disable |
| Detecting Radius: | 12m (mounting height 3m) |
| Mounting Height: | 6m Max |
| Detecting Angle: | 30°~150° |
| Operating Temperature: | -20°C... +60°C |

ACCESSORIES

| | |
|--------------------------------|--|
| 95545, Hero chrome bezel | 95550, Hero black grill bezel |
| 95546, Hero white eyelid bezel | 95551, Hero anthracite grey plain bezel |
| 95547, Hero white grill bezel | 95552, Hero anthracite grey eyelid bezel |
| 95548, Hero black plain bezel | 95553, Hero anthracite grey grill bezel |
| 95549, Hero black eyelid bezel | |

