

## Safety Data Sheet

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : SX Superglue MV  
UFI : 0D50-705H-5009-R280  
Type of product : ethyl 2-cyanoacrylate  
Product group : Adhesives, sealants

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional use, Consumer use  
Use of the substance/mixture : Adhesives, binding agents  
Function or use category : Adhesives, binding agents

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Siroflex Limited  
Dodworth Business Park  
Dodworth, Barnsley  
S75 3SP  
Tel: 01226 771600  
www.siroflex.co.uk info.siroflex@bostik.com

#### 1.4. Emergency telephone number

Emergency number : +44 (0)1226 771600  
Office hours only

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2 H319  
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335  
Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

May cause respiratory irritation.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Contains

: ETHYL-2-CYANOACRYLATE

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

- Hazard statements (CLP) : H315 - Causes skin irritation.  
 H319 - Causes serious eye irritation.  
 H335 - May cause respiratory irritation.
- Precautionary statements (CLP) : P102 - Keep out of reach of children.  
 P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.  
 P264 - Wash hands thoroughly after handling.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P280 - Wear eye protection.  
 P302+P352 - IF ON SKIN: Wash with plenty of soap and water.  
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 - Call a doctor, a POISON CENTER if you feel unwell.  
 P321 - Specific treatment (see supplemental first aid instruction on this label).  
 P332+P313 - If skin irritation occurs: Get medical advice.  
 P337+P313 - If eye irritation persists: Get medical advice.  
 P362+P364 - Take off contaminated clothing and wash it before reuse.  
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P405 - Store locked up.  
 P501 - Dispose of contents/container to contents and container hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- EUH-statements : EUH202 - Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

### 2.3. Other hazards

Other hazards which do not result in classification : None under normal conditions.  
 vPvB: not relevant – no registration required

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ETHYL-2-CYANOACRYLATE	(CAS-No.) 7085-85-0 (EC-No.) 230-391-5 (EC Index-No.) 607-236-00-9 (REACH-no) 01-2119527766-29	70 – 95	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
HYDROQUINONE	(CAS-No.) 123-31-9 (EC-No.) 204-617-8 (EC Index-No.) 604-005-00-4 (REACH-no) 01-2119524016-51	0.09	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Muta. 2, H341 Carc. 2, H351 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
ETHYL-2-CYANOACRYLATE	(CAS-No.) 7085-85-0 (EC-No.) 230-391-5 (EC Index-No.) 607-236-00-9 (REACH-no) 01-2119527766-29	( 10 ≤C < 100) STOT SE 3, H335

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Exothermic reaction on contact with : - Skin contact.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation. May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.
Symptoms/effects after skin contact	: Irritation. Rednesses.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Clean up any spills as soon as possible, using an absorbent material to collect it.
------------------	---

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Avoid breathing dust, fume, gas, mist, spray, vapours.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment.
Emergency procedures	: Ventilate the area thoroughly. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

## 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing dust, fume, gas, mist, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation, especially in confined areas.

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Incompatible products : Strong bases.

Incompatible materials : Water.

### 7.3. Specific end use(s)

adhesives.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

#### MXBON 401

##### Austria - Occupational Exposure Limits

Local name	Cyanacrylsäureethylester
MAK (OEL TWA)	9 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	2 ppm
Regulatory reference	BGBl. II Nr. 186/2015

##### Belgium - Occupational Exposure Limits

Local name	2-Cyanoacrylate d'éthyle # Ethyl-2-cyanoacrylaat
OEL TWA	1.04 mg/m <sup>3</sup>
OEL TWA [ppm]	0.2 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018

##### Bulgaria - Occupational Exposure Limits

Local name	Хидрохинон
OEL TWA	2 mg/m <sup>3</sup>
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.73 от 4 септември 2018 г.)

##### Croatia - Occupational Exposure Limits

Local name	Etil-cijanoakrilat
KGVI (OEL STEL)	1.5 mg/m <sup>3</sup>
KGVI (OEL STEL) [ppm]	0.3 ppm
Naznake (HR)	Koža (razvrstana kao tvar koja nadražuje kožu (H315))

MXBON 401	
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Ethylcyanoacrylat
OEL TWA [1]	10 mg/m <sup>3</sup>
OEL TWA [2]	2 ppm
Regulatory reference	BEK nr 655 af 31/05/2018
<b>Estonia - Occupational Exposure Limits</b>	
Local name	Etüülsüanoakrülaat
OEL TWA	10 mg/m <sup>3</sup>
OEL TWA [ppm]	2 ppm
OEL STEL	20 mg/m <sup>3</sup>
OEL STEL [ppm]	4 ppm
Regulatory reference	Vabariigi Valitsuse 18. septembri 2001. a määruse nr 293 (RT I, 30.11.2011, 5)
<b>Finland - Occupational Exposure Limits</b>	
Local name	Etyyli-2-syanoakrylaatti
HTP (OEL TWA) [1]	1 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	0.2 ppm
Regulatory reference	HTP-ARVOT 2018 (Sosiaali- ja terveystieteiden ministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Hydroquinone
VME (OEL TWA)	2 mg/m <sup>3</sup>
Note (FR)	Valeurs recommandées/admises; substance classée cancérogène de catégorie 2 et mutagène de catégorie 2
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Greece - Occupational Exposure Limits</b>	
Local name	Υδροκινόνη
OEL TWA	2 mg/m <sup>3</sup>
OEL STEL	4 mg/m <sup>3</sup>
Regulatory reference	Π.Δ. 90/1999
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Ethyl cyanoacrylate
OEL TWA [2]	0.2 ppm
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Etil-2-cianakrilatas
IPRV (OEL TWA)	10 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	2 ppm
TPRV (OEL STEL)	20 mg/m <sup>3</sup>
TPRV (OEL STEL) [ppm]	4 ppm

MXBON 401	
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
<b>Poland - Occupational Exposure Limits</b>	
Local name	2-Cyanoakrylan etylu
NDS (OEL TWA)	1 mg/m <sup>3</sup>
NDSch (OEL STEL)	2 mg/m <sup>3</sup>
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Portugal - Occupational Exposure Limits</b>	
Local name	Cianoacrilato de etilo
OEL TWA [ppm]	0.2 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Romania - Occupational Exposure Limits</b>	
Local name	1,4-dihydroxibenzen/Hidrochinonă
OEL TWA	1 mg/m <sup>3</sup>
OEL STEL	2 mg/m <sup>3</sup>
Regulatory reference	Hotărârea nr. 584/2018
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	Hydrochinón (benzén-1,4-diol)
NPHV (OEL TWA) [1]	2 mg/m <sup>3</sup>
Upozornenie (SK)	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Regulatory reference	Nariadenie vlády č. 33/2018 Z.z.
<b>Spain - Occupational Exposure Limits</b>	
Local name	Cianoacrilato de etilo
VLA-ED (OEL TWA) [2]	0.2 ppm
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Etyl-2-cyanoakrylat
NGV (OEL TWA)	10 mg/m <sup>3</sup>
NGV (OEL TWA) [ppm]	2 ppm
KTV (OEL STEL)	20 mg/m <sup>3</sup>
KTV (OEL STEL) [ppm]	4 ppm
Anmärkning (SE)	M (Medicinska kontroller kan krävas för hantering av ämnet. Se vidare föreskrifterna om medicinska kontroller i arbetslivet. För vissa ämnen ska arbetsgivaren erbjuda läkarundersökning och för andra ämnen gäller krav på periodisk läkarundersökning och tjänstbarhetsbedömning); S (Ämnet är sensibiliserande. Sensibiliserande ämnen kan ge allergi eller annan överkänslighet. Överkänslighetsbesvären drabbar främst huden eller andningsorganen. Överkänslighet innebär att man reagerar vid kontakt med ämnen som normalt inte ger besvär. Allergi är en undergrupp av överkänslighet som orsakas av reaktioner i kroppens immunsystem. Särskilt låga gränsvärden har fastställts för ämnen med mer uttalat luftvägssensibiliserande egenskaper. Några ämnen med starkt sensibiliserande egenskaper får endast hanteras efter tillstånd från Arbetsmiljöverket, se föreskrifterna om kemiska arbetsmiljörisker. Dessa ämnen har inga gränsvärden men i vissa fall riktvärden); V (Vägledande kortidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)

MXBON 401	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethyl cyanoacrylate
WEL STEL	1.5 mg/m <sup>3</sup>
WEL STEL (ppm)	0.3 ppm
Regulatory reference	EH40/2005 (Third edition, 2018). HSE
<b>Iceland - Occupational Exposure Limits</b>	
Local name	Etýlsýanóakrylát
OEL TWA	10 mg/m <sup>3</sup>
OEL TWA [ppm]	2 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
<b>Norway - Occupational Exposure Limits</b>	
Local name	Hydrokinon
Grenseverdi (OEL TWA) [1]	0.5 mg/m <sup>3</sup>
Merknader (NO)	A (Kjemikalier som skal betraktes som at de fremkaller allergi eller annen overfølsomhet i øynene eller luftveier, eller som skal betraktes som at de fremkaller allergi ved hudkontakt); K (Kjemikalier som skal betraktes som kreftfremkallende)
Regulatory reference	FOR-2018-08-21-1255
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	2-Cyanoacrylate d'éthyle / Cyanacrylsäureethylester [Ethyl-2-cyanoacrylat]
MAK (OEL TWA) [1]	9 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	2 ppm
Critical toxicity	VRS, Peau / OAW, Haut
Regulatory reference	www.suva.ch, 01.07.2019

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.

#### Personal protective equipment symbol(s):

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



**8.2.2.1. Eye and face protection**

<b>Eye protection:</b>
Safety glasses

**8.2.2.2. Skin protection**

<b>Skin and body protection:</b>
Wear suitable protective clothing

<b>Hand protection:</b>
Protective gloves

**8.2.2.3. Respiratory protection**

<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

**8.2.2.4. Thermal hazards**

No additional information available

**8.2.3. Environmental exposure controls**

**Environmental exposure controls:**

Avoid release to the environment.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Colour	: Colourless.
Odour	: Characteristic odour.
Odour threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No available data
Freezing point	: No data available
Boiling point	: > 149 °C
Flash point	: 80 – 93.4 °C Closed cup
Critical temperature	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable. Not applicable
Vapour pressure	: 0.27 mbar
Vapour pressure at 50 °C	: < 0.7 bar
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 1.05
Relative gas density	: No data available



# Safety Data Sheet

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Solubility : No data available.  
 Water: No data available  
 Ethanol: No data available  
 Ether: No data available  
 Acetone: No data available  
 Organic solvent: No data available

Partition coefficient n-octanol/water (Log Pow) : No data available

Viscosity, kinematic : ≈ 90 mm<sup>2</sup>/s

Viscosity, dynamic : ≈ 100 mPa·s

Explosive properties : No data available.

Oxidising properties : No data available.

Explosive limits : No data available

## 9.2. Other information

VOC content : < 3 %

Additional information : No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Strong bases. Incompatible with water, humid air.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

#### MXBON 401

LD50 oral rat	> 5000 mg/kg
LD50 dermal	> 2000 mg/kg

#### ETHYL-2-CYANOACRYLATE (7085-85-0)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

## HYDROQUINONE (123-31-9)

LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
--------------------	---

Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable.
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.

## ETHYL-2-CYANOACRYLATE (7085-85-0)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

## MXBON 401

Viscosity, kinematic	≈ 90 mm <sup>2</sup> /s
----------------------	-------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

## HYDROQUINONE (123-31-9)

LC50 - Fish [1]	0.638 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Daphnia [1]	0.134 mg/l Test organisms (species): Daphnia magna
EC50 - Daphnia [2]	0.061 mg/l Test organisms (species): Daphnia magna

### 12.2. Persistence and degradability

#### MXBON 401

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### MXBON 401

Bioaccumulative potential	Not established.
---------------------------	------------------

**12.4. Mobility in soil**

**MXBON 401**

Mobility in soil	No data available
------------------	-------------------

**12.5. Results of PBT and vPvB assessment**

**MXBON 401**

vPvB: not relevant – no registration required

**12.6. Other adverse effects**

Additional information : No other effects known


**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Regional legislation (waste) : Disposal must be done according to official regulations.  
 Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
 European List of Waste (LoW) code : 08 04 09\* - waste adhesives and sealants containing organic solvents or other dangerous substances

**SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not regulated	Not regulated	UN 3334	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Aviation regulated liquid, n.o.s. (ethyl 2-cyanoacrylate)	Not regulated	Not regulated
<b>Transport document description</b>				
Not regulated	Not regulated	UN 3334 Aviation regulated liquid, n.o.s. (ethyl 2-cyanoacrylate), 9, III	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	9	Not regulated	Not regulated
Not regulated	Not regulated		Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	III	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Dangerous for the environment : No	Not regulated	Not regulated
No supplementary information available				

# Safety Data Sheet

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

## 14.6. Special precautions for user

### Overland transport

Not regulated

### Transport by sea

Not regulated

### Air transport

- PCA Excepted quantities (IATA) : E1
- PCA Limited quantities (IATA) : Y964
- PCA limited quantity max net quantity (IATA) : 30kgG
- PCA packing instructions (IATA) : 964
- PCA max net quantity (IATA) : 100L
- CAO packing instructions (IATA) : 964
- CAO max net quantity (IATA) : 220L
- Special provisions (IATA) : A27
- ERG code (IATA) : 9A

### Inland waterway transport

Not regulated

### Rail transport

Not regulated

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

- Contains no REACH substances with Annex XVII restrictions
- Contains no substance on the REACH candidate list
- Contains no REACH Annex XIV substances
- Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.
- Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : < 3 %

#### 15.1.2. National regulations

##### France

##### Occupational diseases

Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma

##### Germany

- Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

##### Netherlands

- SZW-lijst van kankerverwekkende stoffen : None of the components are listed
- SZW-lijst van mutagene stoffen : None of the components are listed
- NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
- NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
- NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

# Safety Data Sheet

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**Denmark**

- Class for fire hazard : Class III-1
- Store unit : 50 liter
- Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out

**SECTION 16: Other information**

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Muta. 2	Germ cell mutagenicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH202	Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.