CentaurPlus C17 Series 2

Electronic time control

CentaurPlus single channel, 7-day control suitable for combi boiler applications, an extra heating zone, or the pump on a solid fuel boiler. Highly popular and affordable, the latest Series 2 units now feature an upgraded back-lit display screen and incorporate an automatic GMT/ BST clock.

All models feature an industry standard six-pin backplate, which permits easy replacement/upgrade, with the C17 being suitable for use with combi boilers and the C27 being ideal for non-combi boiler installations, where a hot water cylinder is in use.



Applications

- Control of most domestic gas or oil-fired central heating
 7-day programming and hot water systems.
- Combination ('combi') boiler systems
- Stored hot water systems
- Solid-fuel systems
- Additional zone control

Benefits

- Standard wall plate simple to plug-in and replace
- Direct replacement for many competitor products

Features

- Up to 3 On/Off's a day
- Hot water boost and central heating advance
- Programme options: On, Off, All-day or Auto
- Mains powered with battery back-up
- 7 years no quibbles warranty









CentaurPlus C17 Series 2



Technical specifications

Electrical

Contact rating 3 (1) Amps 230V AC

Contact type Micro-disconnection voltage-free

Rated impulse voltage Cat 2 - 2500V Supply 230V AC 50Hz only

Environmental

Pollution degree Degree 2 Class a software Type 1 Control 0 °C to +40 °C Operating temperature range

Battery life Minimum 10 months continuous operation

Mechanical

Case material Thermoplastic flame retardant

84 x 150 x 29mm **Dimensions**

Features

Display Back-lit liquid crystal

12-hour am/pm Auto BST/GMT changeover Clock

Displayed time adjustments 1-minute steps Switched time adjustments 10-minute steps

Operating periods 3 per-day per-channel. Separate programmes possible for each day of the

Override 1-hour boost, 1-hour extension to On period, instant advance

Mounting 6 terminal plug-in wall plate

Operating periods per-day 3 for each channel

Override (each channel) 1 or 2-hour boost, 1 or 2-hour extension to On period, instant advance

Enclosure protection Flame retardant thermoplastic