CentaurPlus C27 Series 2

Electronic time control

CentaurPlus C27 is a 2 channel 7-day control, allowing independent time control of central heating and hot water. Highly popular and affordable, with the latest Series 2 now featuring a backlit display, and incorporating an automatic GMT/BST clock.

All models feature an industry standard six-pin backplate which permits easy replacement/upgrade. The C17 is suitable for use with combi boilers, and the C27 is ideal for non-combi boiler installations where a hot water cylinder is in use.



Applications

- Control of most domestic gas or oil-fired central heating and hot water systems.
- Combination ('combi') boiler systems
- Stored hot water systems
- Solid-fuel systems
- Additional zone control

Benefits

- Standard wall plate simple to plug-in and replace
- Direct replacement for many competitor products

Features

- 7-day programming
- Up to 3 On/Off's a day
- Hot water boost and central heating advance
- Programme options: On, Off, All day or Auto
- Mains powered with battery back-up
- 7 years no quibbles warranty





CentaurPlus C27 Series 2



Technical specifications

Electrical

Contact rating Contact type Rated impulse voltage Supply

Environmental

Pollution degree Class a software Operating temperature range Battery life

Mechanical

Case material Dimensions

Features

Display	Back-lit liquid crystal
Clock	12-hour am/pm Auto BST/GMT changeover
Displayed time adjustments	1-minute steps
Switched time adjustments	10-minute steps
Operating periods	3 per-day per-channel. Separate programme week
Override	C17: 1-hour boost, 1- hour extension to On p

Mounting Enclosure protection

eparate programmes possible for each day of the C17: 1-hour boost, 1- hour extension to On period & Instant advance C27: 1-hour boost (HW only), 1-hour extension to On period (HW only) and instant advance (CH only) 6 terminal plug-in wall plate

Flame retardant thermoplastic

3 (1) Amps 230V AC

230V AC 50Hz only

Cat 2 - 2500V

Degree 2

Type 1 Control

0 °C to +40 °C

84 x 150 x 29mm

Micro-disconnection Voltage-free C17 only)

Minimum 10 months continuous operation

Thermoplastic flame retardant

Australia

sales_australia@securemeters.com sales_middleeast@securemeters.com www.securemeters.com/au

Middle East www.securemeters.com/me

Europe sales_europe@securemeters.com www.securemeters.com/eu

India, Asia, Africa sales_india@securemeters.com www.securemeters.com/in

UK

sales_uk@securemeters.com www.securemeters.com/uk

www.securemeters.com