

Onyx 50W flood

EL50X3F



PRODUCT DATA

LUMENS (lm)	6500lm
WATTAGE (W)	50W
COLOUR TEMPERATURE (K)	5000K
WEIGHT (kg)	1.15kg
BEAM ANGLE	120°
WINDAGE	0.07m ²
CRI	>70
REPLACEMENT FOR	75W HID Lamp
DIMENSIONS (mm)	230x191x45mm
PRODUCT TYPE	Floods
EFFICIENCY (lm/w)	130lm/W
RATED LIFETIME (hrs)	25,000hrs
IP	65
IK	07
HOUSING COLOUR	Black
WORKING ENVIRONMENT	-20°C to 40°C
WARRANTY	2 years


KEY FEATURES

The high output of the Onyx 50W flood (3rd generation) makes it a perfect replacement for a 75W HID Lamp and is ideal as a high powered floodlight. The input voltage range of 110-240Vac allows for use in both commercial, industrial and construction site lighting. Additionally, by using our optional coastal marine upgrade version, users are able to install the Onyx in coastal marine areas (Code: LL001).


COMMERCIAL APPLICATIONS

For external use on: Warehouses, factories, sports facilities, retail outlets, car-parks, construction sites, footpaths, parks, loading bays. Not suitable for swimming pool areas or for use as a low bay or high bay - please contact us for information on our products which are suitable.

POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS

