

# Solray Select LED Batten 4ft 20-34W

### EL4SR2B



#### PRODUCT DATA

LUMENS (Im)	5200lm	
WATTAGE (W)	20-34W	
COLOUR TEMPERATURE (K)	4000K	
WEIGHT (kg)	1.3kg	
BEAM ANGLE	110° x 130°	
CRI	>85	
REPLACEMENT FOR		
Single or Twin T8 36W 4ft and Single	e or twin T5 54W 4ft	
DIMENSIONS (mm)	1230 x 60 x 74mm	
PRODUCT TYPE	Linear battens	
EFFICIENCY (Im/w)	Up to 160lm/W	
RATED LIFETIME (hrs)	50,000hrs	
IP	20	
HOUSING COLOUR	RAL9003	
WORKING ENVIRONMENT	-20°C to 35°C	
WARRANTY	5 year	
L70 RATING (hrs)	>80000hrs	

# SELECTABLE SETTINGS

WATTAGE	LUMENS	WATTAGE	LUMENS
20W	3200lm		
25W	3900lm		
30W	4600lm		
34W	5200lm		


#### **KEY FEATURES**

Perfect for new installations and like-for-like replacements, this batten allows the client to choose the light level that they require during the installation process. This exciting development means that the Solray Select is equivalent to both Single and Twin T5 Fluorescent Tubes with lumen range of 3200-5200 lumens. The flicker free operation, BESA mounting and M20 cable entry allow the unit to easily replace older fluorescent models.

# COMMERCIAL APPLICATIONS

Offices, schools, corridors, medical centres


#### POLAR CURVE DIAGRAM



E(C90) 56.6° 467 E(C90) 68.0° 147 E(0°) 1397 E(080) 68.6° 117 E(00) 68.0° 37

E(0°) 68.6° 52 E(C0) 68.0° 16 E(0°) 349 E(C90) 56.6° 29 E(C0) 68.0° 9

E(0°) 223 E(090) 56.6° 19 E(00) 68.0° 6 E(C90) 56.6° 13 E(C0) 68.0° 4



## **DIMENSIONS**

