

Barracuda Xtreme Freezer Select 5ft Non Corrosive

EL5CTHBNC3



PRODUCT DATA

LUMENS (lm)	8000lm
WATTAGE (W)	29-52W
COLOUR TEMPERATURE (K)	4000/5000/6500K
WEIGHT (kg)	2.1kg
BEAM ANGLE	115°
CRI	>85
REPLACEMENT FOR	Single/Twin 5ft T8 Tube 58W
DIMENSIONS (mm)	1560x100x82mm
PRODUCT TYPE	Non-corrosives
EFFICIENCY (lm/w)	Up to 169lm/W
RATED LIFETIME (hrs)	50,000hrs
IP	66
IK	08
HOUSING COLOUR	Grey
WORKING ENVIRONMENT	-35°C - 40°C
WARRANTY	3
L70 RATING (hrs)	>80,000hrs

SELECTABLE SETTINGS

WATTAGE	LUMENS	WATTAGE	LUMENS
29W	4900lm		
37W	6000lm		
44W	7000lm		
52W	8000lm		


KEY FEATURES

The 5ft **Barracuda Xtreme Low Temperature Non-Corrosive** features four selectable power and three colour option outputs at the point of installation via a switch on the driver. The product is lightweight and incredibly robust with stainless steel clips supplied. This product can be fitted in a wide range of industrial and commercial applications and its IP66 and IK08 ratings will ensure that it works in extreme environments. Not suitable for use with PIR or Microwave sensor technology when used below -18°C


COMMERCIAL APPLICATIONS

manufacturing plants, furnaces, clay ovens, industrial bakeries, refineries, food processing factories, freezers, cold stores

POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS





+44 (0)1928 242 918 | sales@novah.co.uk | www.novah.co.uk

