## **X**nightsbridge


## **DATASHEET**



## **CL5KW**

Smart 5W LED RGB and CCT SES Candle Lamp -

www.mlaccessories.co.uk



The second color	MLA PART CODE	CL5KW
White   FFUSER	DESCRIPTION	Smart 5W LED RGB and CCT SES Candle Lamp - 38mm
FFUSER         Frosted           MENSIONS (MM)         Diameter - 38 Height - 112           DNSTRUCTION         Construction - Polycarbonate           RATING         IP20           ATTAGE (W)         5           AMP TECHNOLOGY         LED           AMP BASE         E14           JUMENS (LM)         440           JUMEN TOLERANCE         5%           FFICACY (LM/W)         91.3           RCUIT WATTAGE (W)         4.8           CT         4000K           GHT COLOUR         RGBW           RI         >85           DCM         <6           JUNNING CURRENT (A)         0.04           SPLACEMENT FACTOR         >0.7           VM         0.001           ST-LM         0.01           FE SPAN (HRS)         15,000	NET WEIGHT (KG)	0.03
Diameter - 38	FINISH	White
Height - 112	DIFFUSER	Frosted
RATING IP20 ATTAGE (W) 5 AMP TECHNOLOGY LED AMP BASE E14 JMENS (LM) 440 JMEN TOLERANCE 5% FFICACY (LM/W) 91.3 RCUIT WATTAGE (W) 4.8 CT 4000K GHT COLOUR RGBW RI >85 DCM <6 JUNNING CURRENT (A) 0.04 SPLACEMENT FACTOR >0.7 VM 0.001 ST-LM 0.01 FE SPAN (HRS) 15,000	DIMENSIONS (MM)	
ATTAGE (W)  AMP TECHNOLOGY  LED  AMP BASE  E14  JMENS (LM)  JMEN TOLERANCE  FFICACY (LM/W)  RCUIT WATTAGE (W)  CT  4000K  GHT COLOUR  RGBW  RI  >85  DCM  <6  JUNNING CURRENT (A)  SPLACEMENT FACTOR  /M  0.001  ST-LM  15,000	CONSTRUCTION	Construction - Polycarbonate
AMP TECHNOLOGY  AMP BASE  E14  JMENS (LM)  JMEN TOLERANCE  FICACY (LM/W)  RCUIT WATTAGE (W)  CT  4000K  GHT COLOUR  RGBW  RI  >85  DCM  <6  JUNNING CURRENT (A)  SPLACEMENT FACTOR  70.001  ST-LM  D.001  FE SPAN (HRS)  E14  440  440  440  440  440  440  440	IP RATING	IP20
### BASE #### E14  #### JMENS (LM) #### 440  JMEN TOLERANCE ##### 5%  #############################	WATTAGE (W)	5
JMENS (LM)       440         JMEN TOLERANCE       5%         FFICACY (LM/W)       91.3         RCUIT WATTAGE (W)       4.8         CT       4000K         GHT COLOUR       RGBW         RI       >85         DCM       <6         JUNNING CURRENT (A)       0.04         SPLACEMENT FACTOR       >0.7         /M       0.001         ST-LM       0.01         FE SPAN (HRS)       15,000	LAMP TECHNOLOGY	LED
JMEN TOLERANCE       5%         FFICACY (LM/W)       91.3         RCUIT WATTAGE (W)       4.8         CT       4000K         GHT COLOUR       RGBW         RI       >85         DCM       <6         JUNNING CURRENT (A)       0.04         SPLACEMENT FACTOR       >0.7         VM       0.001         ST-LM       0.01         FE SPAN (HRS)       15,000	LAMP BASE	E14
### FICACY (LM/W)  ### RCUIT WATTAGE (W)  ### CT	LUMENS (LM)	440
### RCUIT WATTAGE (W)  #### CT ### 4000K  ### GHT COLOUR  ### RGBW  ### SES  ### COLOUR  ### SES  ### COLOUR  ### COLOUR  ### SES  ### COLOUR  ### COL	LUMEN TOLERANCE	5%
### ### ##############################	EFFICACY (LM/W)	91.3
GHT COLOUR       RGBW         RI       >85         DCM       <6	CIRCUIT WATTAGE (W)	4.8
SPLACEMENT (A)   SPLACEMENT FACTOR   ST-LM   0.01	ССТ	4000K
OCM       <6         UNNING CURRENT (A)       0.04         SPLACEMENT FACTOR       >0.7         VM       0.001         ST-LM       0.01         FE SPAN (HRS)       15,000	LIGHT COLOUR	RGBW
UNNING CURRENT (A)       0.04         SPLACEMENT FACTOR       >0.7         VM       0.001         ST-LM       0.01         FE SPAN (HRS)       15,000	CRI	>85
SPLACEMENT FACTOR         >0.7           VM         0.001           ST-LM         0.01           FE SPAN (HRS)         15,000	SDCM	<6
0.001       ST-LM       0.01       FE SPAN (HRS)       15,000	RUNNING CURRENT (A)	0.04
ST-LM         0.01           FE SPAN (HRS)         15,000	DISPLACEMENT FACTOR	>0.7
FE SPAN (HRS) 15,000	SVM	0.001
	PST-LM	0.01
MMABLE Yes*	LIFE SPAN (HRS)	15,000
	DIMMABLE	Yes*
PUT VOLTAGE 230V 50Hz	INPUT VOLTAGE	230V 50Hz
ONNECTIVITY Wi-Fi + BLE	CONNECTIVITY	Wi-Fi + BLE
ARRANTY 2year(s)	WARRANTY	2year(s)







ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270811407

Date Created: 04/04/2022 12:31





