



Mulu

Mulu, Standard IP65 LED emergency exit sign bulkhead

Kosnic's LED Emergency Exit Sign or Emergency Bulkhead Luminaire is a self-contained, multi-purpose, non-maintained or maintained*3-hour emergency exit sign or emergency luminaire solution. The fitting can be used with or without the emergency exit graphics. It is supplied with adaptable self-adhesive graphics that can be arranged to indicate escape routes as necessary.

MUL0105 ()

Specification

Voltage (eg 220-240 Vac 50/60Hz)	220-240 Vac 50-60 Hz
Current (mA)	46
Rated Power (W)	5
CCT Words	Day Light
CCT (K)	6500
Beam Angle(°)	120
Nominal Lifetime (h)	40000
Total Luminous Flux (lm)	160 (maintained, no graphics), 150 (emergency, no graphics), 80 (maintained, with graphics), 70 (emergency, with graphics)
Power Factor	0.45
Dimensions L x W x D (mm)	352 x 110 x 68
Protection Rating	Class II
IP Rating	IP65
Ambient Temperature Range (°C)	-10 to 40
Battery Capacity	1500 mAh
Battery Charging Time	12 hours
Battery Code	BAT15NC3
Battery Life	4 years
Battery Type	Nickel Cadmium
Battery Voltage	3.6V
Emergency Operating Time	3 hours
Emergency Conversion Time	1 second
Emergency Operation Test	Manual

Light Source Specification

Lumen Maintenance Factor (x.xx)	0.75
---------------------------------	------

Optional Gears and Accessories

Accessories 1	BAT15NC3
---------------	----------

Technical Drawings

