



Push-wire terminal block included



Mauna



Toba

## Neka

### Neka Universal Non-maintained emergency kit for downlights

- Compatible with Kosnic downlights • Non-Maintained • Three hour rated duration • Class II, IP20 (IP65 when installed with a recessed mounted downlight) • Self-Adhesive LED Pad • Push-wire terminal block included • Green charging status LED • 4 years battery life • Built-in Li-Ion Battery • Mercury free

**EMPAD01 (06470) (06470)**

## Specification

Battery Warranty 4 Years

## UEM/EME

UEM/EME Input Power (Max) (W)	2
UEM/EME Input Voltage	220-240 Vac 50-60 Hz
UEM/EME Input Current (Max) (mA)	26
UEM/EME Battery Output Wattage (W)	1
UEM/EME Protection	Class II, IP20, (IP65 when installed with a recessed mounted downlight)
UEM/EME Battery Code	KBAT2000LI1
UEM/EME Battery Voltage (Vdc)	3.6
UEM/EME Battery Type	Li-ion
UEM/EME Battery Capacity (mAh)	2000
UEM/EME Battery Charging Time (h)	24
UEM/EME Battery Life (Years)	4
UEM/EME Emergency Conversion time (s)	1
UEM/EME Emergency Operation time (h)	3
UEM/EME Emergency Operation Test	Manual
UEM/EME Dimensions L x W x D (mm)	175 x 35 x 40
UEM/EME Weight (g)	155
UEM/EME Ambient Temperature Range (°C)	0 to 45
UEM/EME Power Factor	0.50
UEM/EME Luminous Flux	100 lm
UEM/EME LMF at Nominal Lifetime	0.75
UEM/EME CCT	6000k Day Light
UEM/EME Warm-up time to 60%	Instant full light
UEM/EME Lifetime (h)	30000 h

## Technical Drawings

