



Alto

Alto 30W Wall pack with integrated LED

Kosnic's LED Wall Pack Bulkhead offers a low maintenance and robust solution to external lighting for commercial and industrial buildings in applications such as perimeter lighting, pedestrian lighting and vehicle access area lighting. The bulkhead is available with a built-in dusk to dawn sensor, that will turn the light on at low ambient light levels, or a microwave presence sensor. It has a metal base, a polycarbonate opal diffuser and is IP65 rated.

ALT30-SCT (06202)

Specification

Voltage	220-240Vac 50-60Hz
Voltage (eg 220-240 Vac 50/60Hz)	220-240Vac 50/60Hz
Current (mA)	137
Rated Power (W)	30
CCT Words	Cool White (Warm White, Day Light)
CCT (K)	4000 (3000, 6500)
Nominal Lifetime (h)	50000
L70B50 Lifetime (h)	50000
L80B10 Lifetime (h)	50000
Total Luminous Flux (lm)	2900 (2700, 2700)
Power Factor	0.95
Blue Light Hazard	RG1
Glow wire temperature(°C)	650
UGR	N/A
Dimensions L x W x D (mm)	309 x 264 x 115 mm
Weight (kg)	1.8
In-rush current (peak/duration) (A)	14A 360µs
Protection Rating	Class I
Length (mm)	309
IK Rating	IK10
IP Rating	IP65
Ambient Temperature Range (°C)	-20-40
Lamp Cap	N/A
Depth (mm)	49

Light Source Specification

Lighting Technology Used	LED
Directional / Non Directional (DLS/NDLS)	NDLS
Light Source Cap Type (or other interface)	Terminal

Mains / Non-Mains (MLS/NMLS)	NMLS
Connected Light source (Y/N)	N
Colour Tunable Light Source (Y/N)	N
High Luminance Light Source (Y/N)	N
Anti-Glare Shield (Y/N)	N
Dimmable (Y/N/Specific dimmer)	N
Energy Consumption in on-mode (kWh/1000H)	27
Energy Efficiency Class (NEW FORMULA)	E
Useful Luminous Flux (lm)	3600 (3300, 3300)
Beam Angle correspondence (in 360°/120°/90°)	in 360°
CCT	4000 (3000, 6500)
On-Mode Power (Pon) (W)	27
Standby Power (Psb) (W)	0
Networked Standby Power (Pnet) (W)	N/A
CRI	82
CRI (min)	80
CRI (max)	84
Height (mm)	300
Width (mm)	264
Depth (mm)	49
Claim of Equivalent Power? (Y/N)	N
Equivalent Power (W)	N/A
Chromaticity Co-Ordinates (X)	0.38 (0.44, 0.313)
Chromaticity Co-Ordinates (Y)	0.38 (0.403, 0.337)
Peak Luminous Intensity (DLS) (cd)	N/A
Beam Angle (DLS)	N/A
Beam Angle (min)(DLS)	N/A
Beam Angle (max) (DLS)	N/A
R9 CRI (LED/OLED)	20 (6, 19)
Survival Factor (x.xx)	0.9

Lumen Maintenance Factor (x.xx)	0.96
Displacement Factor	N/A
Colour Consistency in Mcadam Ellipses (Mains LED/OLED)	N/A
LED light source replaces fluorescent without integrated ballast of particular wattage (Mains LED/OLED) (Y/N)	N/A
Replacement W Claim (Mains LED/OLED) (W)	N/A
Flicker metric (pst LM) (x,x)	N/A
Stroboscopic effect metric (SVM) (x,x)	N/A

Optional Gears and Accessories

Component 1	DD Emergency Module EMDD03
Component 2	Self-Test DD Emergency Module CEC02LBL/S

Technical Drawings

