



GLS

Reon Non-Dimmable LED GLS, B22, 20000 hours, 4000K

The Reon range from Kosnic is a selected line of 20,000 hour, energy saving retrofit LED lamps. Reliable, affordable and easy to install, Reon LEDs surpass the high quality standards that home owners and professionals demand for lower cost applications.

GLS09/B22-N40 ()

Specification

| | |
|----------------------------------|--------------------|
| Voltage (eg 220-240 Vac 50/60Hz) | 220-240Vac 50/60Hz |
| Current (mA) | 71 |
| Rated Power (W) | 9 |
| CCT Words | Cool White |
| CCT (K) | 4000 |
| L70B50 Lifetime (h) | 15000 |
| Total Luminous Flux (lm) | 1000 |
| Power Factor | 0.55 |
| Blue Light Hazard | RG1 |
| Glow wire temperature(°C) | 650 |
| Dimensions L x W x D (mm) | 110* ϕ 60mm |
| Weight (kg) | 0.041 |
| Ambient Temperature Range (°C) | -20 to 40 |
| Depth (mm) | 60 |

Light Source Specification

| | |
|--|---------|
| Lighting Technology Used | LED |
| Directional / Non Directional (DLS/NDLS) | NDLS |
| Light Source Cap Type (or other interface) | B22 |
| Mains / Non-Mains (MLS/NMLS) | MLS |
| Connected Light source (Y/N) | N |
| Colour Tunable Light Source (Y/N) | N |
| High Luminance Light Source (Y/N) | N |
| Anti-Glare Shield (Y/N) | N |
| Dimmable (Y/N/Specific dimmer) | N |
| Energy Consumption in on-mode (kWh/1000H) | 9 |
| Energy Efficiency Class (NEW FORMULA) | E |
| Useful Luminous Flux (lm) | 1000 |
| Beam Angle correspondence (in 360°/120°/90°) | in 360° |

| | |
|---|--------|
| CCT | 4000 |
| On-Mode Power (Pon) (W) | 9 |
| Standby Power (Psb) (W) | 0 |
| Networked Standby Power (Pnet) (W) | N/A |
| CRI | 82 |
| CRI (min) | 80 |
| CRI (max) | 84 |
| Height (mm) | 110 |
| Width (mm) | 60 |
| Depth (mm) | 60 |
| Claim of Equivalent Power? (Y/N) | Y |
| Equivalent Power (W) | 72 |
| Chromaticity Co-Ordinates (X) | 0.3767 |
| Chromaticity Co-Ordinates (Y) | 0.3734 |
| Peak Luminous Intensity (DLS) (cd) | N/A |
| Beam Angle (DLS) | N/A |
| Beam Angle (min)(DLS) | N/A |
| Beam Angle (max) (DLS) | N/A |
| R9 CRI (LED/OLED) | 8 |
| Survival Factor (x.xx) | 0.9 |
| Lumen Maintenance Factor (x.xx) | 0.93 |
| Displacement Factor | 0.8 |
| Colour Consistency in Mcadam Ellipses (Mains LED/OLED) | 6 |
| LED light source replaces fluorescent without integrated ballast of particular wattage (Mains LED/OLED) (Y/N) | N |
| Replacement W Claim (Mains LED/OLED) (W) | N/A |
| Flicker metric (pst LM) (x,x) | 0.1 |
| Stroboscopic effect metric (SVM) (x,x) | 0.02 |

Technical Drawings

