

**GU10 600LM 5.7W 2700K DIMMABLE 36 BEAM INTEGRAL**

ILGU10DC117



The Integral LED High Lumen GU10 range offers a fantastic ratio of value and performance. By incorporating a stylish engineered lens in an affordable GU10, the High Lumen offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED.

**Details**

<b>Barcode:</b>	5055788255567
<b>Quick Order Code:</b>	765552
<b>Category:</b>	Lamps
<b>Range Name:</b>	240V GU10 Base
<b>Product Type:</b>	GU10
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Commercial indoor, Residential indoor
<b>Finish:</b>	Clear
<b>Warranty (Years):</b>	2

**Physical Data**

<b>Product Length (mm):</b>	54
<b>Product Width (mm):</b>	50
<b>Product Weight (g):</b>	27
<b>Optic:</b>	Designed to give a Classic Look
<b>Material:</b>	Plastic and Aluminium heat-sink, Injection moulded diffuser
<b>Base Term:</b>	GU10
<b>Bulb Base:</b>	GU10
<b>Construction:</b>	Plastic White and "Classic look" diffuser lens
<b>Bulb or Luminaire Shape:</b>	Round
<b>Placement / Application:</b>	Indoor, General Lighting
<b>Spot Type:</b>	SMD

**Electrical Data**

<b>Power (W):</b>	5.7
<b>Power Consumption (W) :</b>	5.7
<b>Power Factor:</b>	0.5



<b>Voltage Range (v):</b>	220-240
<b>Wattage equivalent (W):</b>	75
<b>Amperage (mA):</b>	33
<b>Dimming:</b>	Mains dim
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>True Wattage Eq (W):</b>	75
<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	600
<b>Luminous efficacy (lm/W):</b>	95
<b>Peak Intensity (Cd):</b>	1050
<b>Correlated Colour Temperature (CCT) (K):</b>	2700
<b>Colour Temperature:</b>	2700 - Warm
<b>Colour Temperature Name:</b>	Warm
<b>Beam Angle:</b>	36
<b>Colour Rendering Index (CRI):</b>	80
<b>Compatible Dimmers:</b>	Varilight JQP401W
<b>Frequency Range (Hz):</b>	50/60
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	25000
<b>Switching Cycles:</b>	50000
<b>Useful Lumens (lm):</b>	540

## Environment

<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>New Energy Rating:</b>	E
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	40



## Packaging

<b>Barcode:</b>	5055788255567
<b>Single box qty:</b>	1
<b>Package Weight (g):</b>	36
<b>Package Length (mm):</b>	62
<b>Package Width (mm):</b>	48
<b>Package Depth (mm):</b>	48
<b>Inner Carton Barcode:</b>	05055788255628
<b>Qty per Inner Carton :</b>	10
<b>Inner Carton Length (mm):</b>	255
<b>Inner Carton Width (mm):</b>	105
<b>Inner Carton Depth (mm):</b>	70
<b>Outer Carton Barcode:</b>	05055788255680
<b>Qty per Outer Carton:</b>	100
<b>Outer Carton Length (mm):</b>	550
<b>Outer Carton Width (mm):</b>	270
<b>Outer Carton Depth (mm):</b>	165
<b>Qty per euro pallet:</b>	6000