

**CONSTANT CURRENT DRIVER ADJUSTABLE OUTPUT 31-53W 650-1100MA
IP20 DALI - DALI2 - PUSH-DIMM 0-10V DIMMABLE 14-42V OUTPUT INTEGRAL**

ILDRCCA071A



Integral LED Constant Current Drivers are designed and built using highly reliable components to deliver the best performance for commercial and residential lighting applications.

Details

Barcode:	5055788252993
Quick Order Code:	842361
Category:	Drivers
Range Name:	DALI, DALI2, 0 - 10V, Push - DIM
Product Type:	Constant Current
Product Body Finish:	Matt white
Market Segment:	Commercial indoor
Warranty (Years):	3

Physical Data

Product Length (mm):	125
Product Depth (mm):	30
Product Width (mm):	76
Product Weight (g):	185
Material:	Polycarbonate
Placement / Application:	Indoor, LED Lighting

Electrical Data

Power Factor:	0.95
Voltage (V):	14-42
Voltage Range (v):	220-240
Input Current (A):	0.3
Input Voltage (V):	220-240VAC
Output Current (mA):	Adjustable
Output Voltage (V):	14-42
Dimming:	DALI, DALI, DALI2, PUSH-DIMM and 0-10V
Protection Function:	Short Circuit protection, Overload protection, Thermal protection

EN:

EN61347-1, EN61347-2-13, EN55015, EN61547, EN61000-3-2, EN61000-3-3

LVD Certified: Yes

Light Data

Frequency Range (Hz): 50/60

Environment

EN: EN61347-1, EN61347-2-13, EN55015, EN61547, EN61000-3-2, EN61000-3-3

LVD Certified: Yes

CE RoHS: Yes

Hg 0% (Mercury Free): Yes

IP Rating (Ingress Protection): IP20

Lowest Operating Temperature (°C): -20

Maximum Operating Temperature (°C): 45

Packaging

Barcode: 5055788252993

Single box qty: 1

Package Weight (g): 150

Package Length (mm): 165

Package Width (mm): 75

Package Depth (mm): 45

Outer Carton Barcode: 5055788253020

Qty per Outer Carton: 50

Outer Carton Length (mm): 452

Outer Carton Width (mm): 395

Outer Carton Depth (mm): 175