

## Distribution Boards / Domestic Consumer MCB

### SP MCB Break Capacity 20A 6kA Type B



### Technical Specification

<b>Product Code</b>	PBM20B
<b>Feature 1</b>	Type B
<b>Feature 2</b>	Rated Short Circuit Capacity 6kA
<b>Feature 3</b>	Single Pole
<b>Feature 4</b>	Instantaneous Tripping B Curve
<b>Ambient Temperature</b>	-25 to 55
<b>Barcode</b>	5012739648588
<b>CE</b>	Y
<b>Colour</b>	Grey
<b>Company DUNS Number</b>	216156018
<b>Country of Origin</b>	China
<b>Electrical Endurance</b>	4000
<b>Finish body</b>	Matt
<b>Frequency (Hz) max</b>	60
<b>Frequency (Hz) min</b>	50

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)

Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)

<b>Greenbrook Guarantee (Years)</b>	3
<b>HS Code</b>	8536201090
<b>Installation method</b>	Din rail mount
<b>Materials Main Body</b>	Nylon
<b>Mechanical Endurance</b>	10000
<b>Min Order Qty</b>	12
<b>Mounting</b>	Din Rail
<b>No of Poles</b>	1
<b>Operating Temperature Range max C</b>	55
<b>Operating Temperature Range min C</b>	-25
<b>Pack Contents</b>	12
<b>Package Product Max. Length (mm)</b>	230
<b>Package Product Max. Height (mm)</b>	80
<b>Package Product Max. Width (mm)</b>	90
<b>Package Product Weight gross (g)</b>	1382
<b>Product (only) Max. Depth (mm)</b>	76.5
<b>Product (only) Max. Height (mm)</b>	82
<b>Product (only) Max. Width (mm)</b>	18
<b>Product Weight net (g)</b>	110
<b>Protection Type</b>	MCB
<b>Rated Working Voltage</b>	230
<b>Sales Pack Qty</b>	12
<b>Standards</b>	BS EN 60898
<b>Status Indicator</b>	Y
<b>StatusCode</b>	Active
<b>Storage Temperature</b>	-40 - 70
<b>Terminal Capacity</b>	1 - 25
<b>Terminal Connections</b>	1 - 25
<b>Torque Settings</b>	2
<b>Tripping Characteristics</b>	Type B current curve
<b>UKCA</b>	Y
<b>Voltage (VAC) MAX (V)</b>	220

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)

<b>Voltage (VAC) Min (V)</b>	240
<b>Voltage (VAC) Rated (V)</b>	230
<b>Wiring Capacity</b>	1-25