

Distribution Boards / Domestic Consumer MCB

SP MCB Break Capacity 32A 6kA Type B



Technical Specification

Product Code	PBM32B
Feature 1	Type B
Feature 2	Rated Short Circuit Capacity 6kA
Feature 3	Single Pole
Feature 4	Instantaneous Tripping B Curve
Ambient Temperature	-25 to 55
Barcode	5012739648595
CE	Y
Colour	Grey
Company DUNS Number	216156018
Country of Origin	China
Electrical Endurance	4000
Finish body	Matt
Frequency (Hz) max	60
Frequency (Hz) min	50

Tel No: 01279 772 772

Email: sales@greenbrook.co.uk

Website: www.greenbrook.co.uk

Greenbrook Guarantee (Years)	3
HS Code	8536201090
Installation method	Din rail mount
Materials Main Body	Nylon
Mechanical Endurance	10000
Min Order Qty	12
Mounting	Din Rail
No of Poles	1
Operating Temperature Range max C	55
Operating Temperature Range min C	-25
Pack Contents	12
Package Product Max. Length (mm)	230
Package Product Max. Height (mm)	80
Package Product Max. Width (mm)	90
Package Product Weight gross (g)	1382
Product (only) Max. Depth (mm)	76.5
Product (only) Max. Height (mm)	82
Product (only) Max. Width (mm)	18
Product Weight net (g)	110
Protection Type	MCB
Rated Working Voltage	230
Sales Pack Qty	12
Standards	BS EN 60898
Status Indicator	Y
StatusCode	Active
Storage Temperature	-40 - 70
Terminal Capacity	1 - 25
Terminal Connections	1 - 25
Torque Settings	2
Tripping Characteristics	Type B current curve
UKCA	Y
Voltage (VAC) MAX (V)	220

Tel No: 01279 772 772

Email: sales@greenbrook.co.ukWebsite: www.greenbrook.co.uk

Voltage (VAC) Min (V)	240
Voltage (VAC) Rated (V)	230
Wiring Capacity	1-25