

# DATA SHEET


## CONNECTING SWIVEL WITH SWIVEL

for horizontal cable pulling in combination with CW 800 E

Item no.: 10176




**VIDEO**




Capstan winch  
CW 800 E

[Click here Video](#)





[Click here Productinformation](#)

Detailed images:



Application images:



DATA	
ITEM NO.	10176
TOTAL WEIGHT	0,350 kg
DIMENSION	L 144 mm   Ø 30 mm
FORK Ø	12 mm
TENSION LOAD	1500 kg
MATERIAL	Stainless steel
EAN-CODE	9120045475999

### ADVANTAGES

- ✓ **Stainless steel**  
**Corrosion free**
- ✓ **High quality ball bearings**
- ✓ **Top price - performance ratio**
- ✓ **Tensile load 1500 kg**

### DESCRIPTION

The connecting swivel is used to connect RUNPOTEC polyester pulling ropes with the cables to be pulled or the deployed pulling die and to ensure twist compensation. Ideally suited in combination with the RUNPOTEC CW 800 E capstan winch.

Made of stainless steel, with the highest quality ball bearings, make the connecting swivel from RUNPOTEC completely corrosion-free and thus one of the highest quality products on the market.

**! Safety instructions:**  
Not suitable for vertical cable pulling, must not be used to carry or lift loads or persons.

**Optimal application:** for horizontal cable pulling in combination with the CW 800 E capstan winch  
**Application video:** a short, very informative application video can be viewed by scanning the QR code or on [www.runpotec.com](http://www.runpotec.com).  
**Scope of delivery:** Connecting swivel with twist adjustment

### INFORMATION

**Available separately:**  
**POLYESTER cable pulling rope incl. steel cage**  
Rope: Ø 10 mm  
Item no. 10167 - 120 m  
Item no. 10168 - 200 m  
Rope: Ø 12 mm  
Item no. 10120 - 150 m  
Item no. 10121 - 200 m  
Item no. 10122 - 300 m  
Item no. 10123 - 350 m

**Capstan winch CW 800 E + Trolley**  
Item no. 10138

