



|                          |                                    |
|--------------------------|------------------------------------|
| Product designation      | Pushbutton actuator, spring return |
| Product type designation | LPSB10                             |

**General characteristics**

|                          |                          |
|--------------------------|--------------------------|
| Colour                   | White                    |
| Type of positions        | Flush                    |
| Material                 | Aluminium and zinc alloy |
| IEC degree of protection | IP66, IP67 and IP69K     |

**Mechanical features**

|   |                          |                |
|---|--------------------------|----------------|
| Operating force                           | kg-lb                    | <0.5Kg / 1.1lb |
| Mechanical life - spring return actuators | cycles                   | 5000000        |
| Fixing                                    | Without mounting adapter |                |
| Mounting adapter                          | LPXAU120M                |                |


**UL technical data**

|                         |                              |
|-------------------------|------------------------------|
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|------------------------------|

**Ambient conditions**

|             |                       |     |    |     |
|-------------|-----------------------|-----|----|-----|
| Temperature |                       |     |    |     |
|             | Operating temperature | min | °C | -25 |
|             |                       | max | °C | +70 |
|             | Storage temperature   | min | °C | -40 |
|             |                       | max | °C | +85 |

**Dimensions**



**Certifications and compliance**

|            |                     |
|------------|---------------------|
| Compliance | CSA C22.2 n° 14     |
|            | IEC/EN/BS 60947-1   |
|            | IEC/EN/BS 60947-5-1 |
|            | UL508               |

|              |       |
|--------------|-------|
| Certificates | cULus |
|              | RINA  |

**ETIM classification**

Pushbutton actuator, spring return Ø22mm Platinum series metal, flush, white

ETIM 8.0

EC000221 -  
Front element for  
push button