

# SLFM360N

## PIR Presence Detector (Flush Mount)

### Features & Benefits

- Slimline sensor head design
- 360° detection zone for optimum coverage
- IP44 weatherproof rating (internal use only)
- Manual override (Pulse) for extended light on times
- Adjustable time setting
- Adjustable LUX setting
- 75mm diameter ceiling cut-out



### Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP44
Setting Type	Dial
Max Mounting Height (Mtr)	2.5
Presence Detection (Mtr)	4
Motion Detection (Mtr)	8
Detection Angle	360°

# Data sheet

## SLFM360N

Light / PIR Presence Detectors

<b>Hole Cut-Out Size (mm)</b>	75
<b>Standby Consumption</b>	<0.5W
<b>Number of Channels</b>	1
<b>Switch rating</b>	250W LED, 2000W Halogen, 500W Fluorescent
<b>ON Time Adjustment</b>	3 Seconds to 18 Minutes. User Adjustable
<b>Lux Level</b>	1 to 1000
<b>Detection Range (Mtr)</b>	8
<b>Permanent ON Facility</b>	Yes (Pulse Override)
<b>Dusk Till Dawn</b>	No
<b>Multiple Unit Support</b>	Yes (Up to 8 In Parallel)
<b>Cable Entry(s)</b>	Back Entry

### General

<b>Weight (g)</b>	90
<b>Height (mm)</b>	90
<b>Width (mm)</b>	90
<b>Depth (mm)</b>	60
<b>Body Construction</b>	Polycarbonate
<b>Product Colour</b>	White
<b>Accessories (Included)</b>	Terminal Cover
<b>EAN Number</b>	5012483014790
<b>Guarantee Period</b>	3 Years

## Line Diagrams

