

Benefits & Features

- ✓ Modern style zone 1, continual running, decentralised bathroom extractor fan.
- ✓ Protection rating of IP45 and rated for installation in bathroom zones 1 & 2 (wiring needs to be r.c.d. protected).
- ✓ Permanent running trickle speed with high speed boost.
- ✓ Control Options: Run-on timer, humidity sensor.
- ✓ Fitted with a dynamically balanced impeller to maximise airflow, reduce noise and improve wind & draft resistance.
- ✓ Airflow upto 23 l/s (88 m³/h), with an SFP of 0.28 w/l/s.
- ✓ Noise level down to 25 dB(A) at 3m distance from the fan.
- ✓ Can be wall or ceiling mounting.
- ✓ Fitted with an 3.4w German long life, low energy DC motor, backed with a 5 year warranty.




dMEV settings:

- ✓ Trickle speed options: 6, 8 & 13 l/s.
- ✓ Boost speed options: 15 l/s & max.

Technical Data

MODEL	OSEF100-DMEV
Voltage (V)	230
Power (W)	3.4 MAX
Current (A)	0.039
SFP (W/l/s)	0.278
Air Capacity (m ³ /h) [l/s]	88 m ³ /h [23 l/s]
Sound Pressure Level dB(A)*	25

*Sound pressure level measured in free space at a distance of 3 meters from the fan.



Options

OPTION	OSEF100-DMEV	
	T	H
Run-on timer	•	•
Humidity sensor		•

Turn-off Delay Timer Run on timer Adjustable delay from 2 to 30 minutes

Humidity Sensor Humidity sensor activation threshold is adjustable from 60% to 90%
Run on timer Adjustable delay from 2 to 30 minutes

Dimensions

	Ø d	b	h	l	l1
OSEF100-DMEV	99	158	136	81	26

