


Benefits & Features

- /// Powerful, high performance Whirlwind **PLUS** in-line mixed flow extractor fan with built-in mounting bracket.
- /// Can be used for supply and extract ventilation.
- /// 100mm 4" dia connections suitable for both solid and flexible ductwork.
- /// Removable central core for easy cleaning and maintainance.
- /// Casing is made of high-quality durable plastic.
- /// Airflow upto 61 l/s (220 m3/h), with an SFP down to 0.41 w/l/s.
- /// Meets Part L and F of the UK Building Regulations.
- /// Noise level down to 27 dB(A) at 3m distance from the fan.
- /// Control Options: standard or run-on timer.
- /// Two-speed motor allowing for high/low (trickle/boost) speeds.
- /// Fitted with an 25w German long life, low energy motor, backed with a 5 year warranty.



Technical Data

MODEL	OSEF-WW100P/PT	
Speed	Min	Max
Voltage (V)	1 ~ 230	1 ~ 230
Frequency (Hz)	50/60	50/60
Power (W)	23	25
Maximum air flow (m³/h [l/s])	170 (47)	220 (61)
RPM (min ⁻¹)	1980	2545
Sound Pressure Level at 3m (dBa)	27	32
Max. Transported air temperature (°C)	+60	
SEC class	C	
IP rating	IPX4	
Motor IP rating	IPX4	



Options

OPTION	OSEF-WW100P/PT	
	P	PT
Standard (two speed)	•	•
Run-on timer		•

Standard Connect to high & low speeds

Run-on Timer Run on timer Adjustable time from 2 to 30 minutes
Connect to high & low speeds

Dimensions (mm)

Ø d	Ø d1	b	h	l	Weight (kg)
97	164	196	241	303	1.68

