


## Benefits & Features

- /// Powerful, high performance Whirlwind **PLUS** in-line mixed flow extractor fan with built-in mounting bracket.
- /// Can be used for supply and extract ventilation.
- /// 315mm 12" dia connections suitable for both solid and flexible ductwork.
- /// Removable central core for easy cleaning and maintainance.
- /// Casing is made of high-quality durable plastic.  
Airflow upto 486 l/s (1750 m3/h).
- /// Static pressure over 600 Pa.
- /// Noise level down to 47 dB(A) at 3m distance from the fan.
- /// Control Options: standard or run-on timer.
- /// Two-speed motor allowing for high/low (trickle/boost) speeds.
- /// Fitted with an 315w German long life, low energy motor, backed with a 5 year warranty.
- /// 100, 125, 150, 200, 250 & 315mm versions also available.
- /// Fitted with a dynamically balanced impeller to maximise airflow, reduce noise and improve wind & draft resistance.



## Technical Data

MODEL	OSEF-WW315P/PT	
Speed	Min	Max
Voltage (V)	1 ~ 230	1 ~ 230
Frequency (Hz)	50/60	50/60
Power (W)	227	315
Maximum air flow (m³/h [l/s])	1420 (394)	1750 (486)
RPM (min <sup>-1</sup> )	2115	2505
Sound Pressure Level at 3m (dBa)	47	56
Max. Transported air temperature (°C)	+60	
SEC class	-	
IP rating	IPX4	
Motor IP rating	IPX4	



## Options

OPTION	OSEF-WW315P/PT	
	P	PT
Standard (two speed)	•	•
Run-on timer		•

**Standard** Connect to high & low speeds

**Run-on Timer** Run on timer Adjustable time from 2 to 30 minutes  
Connect to high & low speeds

## Dimensions (mm)

Ø d	Ø d1	b	h	l	Weight (kg)
310	323	362	408	445	11.7

