

103174

ShieldSLIM 4CCT

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt white & clear acrylic finish (white bezel included)
- Constructed from steel & aluminium alloy & polycarbonate
- CCT switchable - Three colour temperature to choose from: Warm White (2700/3000K), Cool White (4000K) & Daylight White (6000K)
- Loop-in / Loop-out detachable quick wire push-fit connector
- Fire rated to 30, 60 & 90 minutes
- Tested with insulation cover thickness 270mm
- Suitable for bathroom zone 1 & 2 and used in conjunction with a 30MA RCD
- IP65



SPEC DATA

Product Wattage:	7W
Product Lumen:	600
Lumen/W:	86
Kelvin:	2700/3000/4000/6000K
SDCM:	6
CRI:	80
Dimmable:	Yes
Lifetime (Hours):	30000
Beam Angle:	60°
Power Factor:	0.95
Driver Type:	Constant Current 170mA
Inrush Current at Start Up:	0.98A
Forward Voltage:	27-42V
Energy Rating:	E
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp.:	-20 to 40 Degree
Product Weight (KG):	0.215
Cut-out (mm):	Ø68mm
Minimum Cavity Depth (mm):	48mm
Terminal Block:	4-way quick fit
Class:	2

ACCESSORIES

- 113479, 100W dimmer module
- 113480, 250W dimmer module
- 114590, ShieldPRO bezel satin nickel
- 114591, ShieldPRO bezel chrome
- 114592, ShieldPRO bezel black
- 114593, ShieldPRO bezel antique brass
- 114594, ShieldPRO bezel polished brass
- 114595, ShieldPRO bezel anthracite grey

