


818 CUR/L

Plastic Consumer Unit Relocation



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material	Polycarbonate
Protection class	IP65
Temp. range min	-25 °C
Temp. range max	85 °C
Glow wire test	650 °C
Impact resistance	IK08
External dimensions LxWxH	215x200x95mm
Type	818 CUR/L
UK-Number	818 CUR/L
Product Color	RAL 7035
WISKA-Order no.	10111966
Packing unit	1

Description:

Suitable for relocating up to 10 ways*

Fast self-tapping stainless screws

Terminals**

2102-1201 - Grey 2 conductor DIN-rail terminal with Lever and Push-in up to 4mm

2102-1204 - Blue 2 conductor DIN-rail terminal with Lever and Push-in up to 4mm

2102-1207 - Green/Yellow 2 conductor DIN-rail terminal with Lever and Push-in up to 4mm

2102-1292 - Orange Endplate for 2102

2110-1201 - Grey 2 conductor DIN-rail terminal with Lever and Push-in up to 16mm

2110-1204 - Blue 2 conductor DIN-rail terminal with Lever and Push-in up to 16mm

2110-1207 - Green/Yellow 2 conductor DIN-rail terminal with Lever and push-in up to 16mm

2110-1292 - Orange Endplate for 2110

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

***Each Final ring circuit need to be considered as 2 ways**



****We reserve the right to use alternative push-in terminals to the same standard should there be supply issues.**

17.07.2024

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk