



## Niah

### Niah, 2W Universal Non-maintained emergency kit for LED Panels

Available April 2023 Niah • Non-maintained, >3hrs • Self-Adhesive LED Pad • Fast fit and easy installation

**EMPAD02** (07241)

## Specification

Battery Warranty 4 Years

## UEM/EME

|  |   |
|--|---|
| UEM/EME Input Power (Max) (W)          | 2   |
| UEM/EME Input Voltage                  | 220-240 Vac 50-60 Hz  |
| UEM/EME Input Current (Max) (mA)       | 22  |
| UEM/EME Battery Output Wattage (W)     | 1.5   |
| UEM/EME Protection                     | Class II, IP20, (IP65 when installed with a recessed panel) |
| UEM/EME Battery Code                   | BAT26LI1  |
| UEM/EME Battery Voltage (Vdc)          | 3.6   |
| UEM/EME Battery Type                   | Li-Ion  |
| UEM/EME Battery Capacity (mAh)         | 2600  |
| UEM/EME Battery Charging Time (h)      | 24  |
| UEM/EME Battery Life (Years)           | 4   |
| UEM/EME Emergency Conversion time (s)  | 1   |
| UEM/EME Emergency Operation time (h)   | 3   |
| UEM/EME Emergency Operation Test       | Manual  |
| UEM/EME Dimensions L x W x D (mm)      | 175 x 35 x 40   |
| UEM/EME Weight (g)                     | 155   |
| UEM/EME Ambient Temperature Range (°C) | 0 to 45   |
| UEM/EME Power Factor                   | 0.4   |
| UEM/EME Luminous Flux                  | 200 lm  |
| UEM/EME LMF at Nominal Lifetime        | 0.75  |
| UEM/EME CCT                            | 6000k Day Light   |
| UEM/EME Warm-up time to 60%            | Instant full light  |
| UEM/EME Lifetime (h)                   | 30000   |

## Technical Drawings

