

**7** 7 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only



# Niva III

06932 NIV6FS36

## NIVA III interior batten 6ft Single 36W CCT switchable

- Switchable CCT (3000K/4000K/6000K)
- High efficiency up to 156lm/W
- Switchable wattage
- Optional plug-in emergency module available
- Optional DALI 2 and PUSH dimming
- For single and twin tube batten replacement
- 20mm Conduit entry
- BESA box fitting points
- Easy installation with press and release end caps to open the cover

### Overview

Niva III LED batten utilises high performance LEDs to offer outstanding lumen efficiency. With switchable CCT and are suitable for a wide range of applications including warehouses, factories and garages. The product range also has the option to install an emergency module and microwave sensor.




IP20



### General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal



### Technical Summary

Product Code	NIV6FS36
Input Voltage Supply	220-240Vac 50/60Hz
Default Power	36 W
Power Factor	>0.94
Default CCT	4,000 K
Settable Colour Temperatures	3000k, 4000k, 6000k
SDCM of CCT	<6
CRI	≥82
Dimmable	N
Flicker	<1%
Lumens Output Maximum	5,400 lm
Maximum Efficiency	150 lm/W
Emergency Luminous Flux	500 lm
L80B10 Lifetime (h) @Ta 25 °C	110,000 h
Nominal Lifetime (h)	50,000 h
Weight	1.9Kg
Dimensions (L x W x D) (mm)	1734x61x71



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

**7** Years  
Product Warranty  
UK Only

**2** Years  
On-Site Warranty  
Main-land UK Only

# Niva III



06932 NIV6FS36

## Optional Gear

Product Code	Description	Type
NIV-MWS	NIVA GO plug-in ON/OFF microwave sensor	Microwave Sensor
BEM203	3W standard UEM for linear LED luminaire	Emergency Module
BEM203/ST	3W self-test UEM for linear LED luminaire	Self-test Emergency Module
BEM303	Batten UEM 3W emergency module for battens	Emergency Module
BEM303/ST	Batten UEM 3W Self test emergency module for battens	Self-test Emergency Module
BEM203/DA	Batten UEM DALI-2, 3W emergency module for Kosnic LED batten luminaires	Emergency Module
BEM303/DA	Batten UEM 3W DALI switchable for battens for battens	Emergency Module

## Accessories

Product Code	Description	Type
SUS-BTN04	Suspension for Niva Kasai Kennet Milo Congo Trent Avon Indus, 4 wires included, max. 1m drop	Suspension Kit
SUS04	LED Panel & Slim Line II suspension kit (4 cables per bag)	Suspension Kit
SUS04/25	Suspension kit 2.5m Alden & Nevis & Slim Line II (4 cables per bag)	Suspension Kit

Settable (Default in Bold)		Variable
Rated Power (W)	CCT (K)	Total Luminous Flux (lm)
36	3000	5000
<b>36</b>	<b>4000</b>	<b>5400</b>
36	6000	5000


## Overview

Niva III LED batten utilises high performance LEDs to offer outstanding lumen efficiency. With switchable CCT and are suitable for a wide range of applications including warehouses, factories and garages. The product range also has the option to install an emergency module and microwave sensor.



## General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal



Product Range	Length(mm)	Width(mm)	Height (mm)	Fixing (mm)	Besa Boxes Fixing(mm)
4ft	1170	61	71	965	600
5ft	1470	61	71	1265	600
6ft	1734	61	71	1529	600



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com