



BR72.100	BR112.125	BR152.125
125A	125A	125A
2	2	2
A: 45 mm B: 68 mm C: 47 mm	A: 45 mm B: 105 mm C: 47 mm	A: 45 mm B: 134 mm C: 47 mm
7 fori - holes (1x Ø 9 - 1x Ø 8 - 5x Ø 6)	11 fori - holes (1x Ø 9 - 2x Ø 8 - 2x Ø 7 - 6x Ø 6)	15 fori - holes (1x Ø 9 - 2x Ø 8 - 2x Ø 7 - 10x Ø 6)
1x35mm <sup>2</sup> - 1x25mm <sup>2</sup> 5x10mm <sup>2</sup>	1x35mm <sup>2</sup> - 2x25mm <sup>2</sup> 2x16mm <sup>2</sup> - 6x10mm <sup>2</sup>	1x35mm <sup>2</sup> - 2x25mm <sup>2</sup> 2x16mm <sup>2</sup> - 10x10mm <sup>2</sup>
1.36 W	4.10 W	5.27 W
1.46 W	4.85 W	6.30 W
20	22	22
6	6	6
8	8	8
<b>507N</b>	<b>5011N</b>	<b>5015N</b>
7 fori - holes (2x Ø 6 - 5x Ø 5,3)	11 fori - holes (2x Ø 6 - 9x Ø 5,3)	15 fori - holes (2x Ø 6 - 13x Ø 5,3)



Le morsettiere BOXDIN possono essere fissate a scatto su guida DIN, incluso viene fornito un profilo in plastica per l'isolamento della guida metallica

The terminal post BOXDIN can be fixed on DIN rail included is supplied a plastic profile for the insulation of the metallic rail