

Product Code: VPMB535BK

## **Technical Specification**



Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet







Insert & Housing: Urea

Earth Strap: Mild Steel

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 2

## **General Information**

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Matt Black

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel

Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified

Operating Voltage (AC) 250

Resistive Load Rating (A) Termination Type Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch

Minimum Back Box Depth (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-2

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Supplied with Matt Black plate fixing screws.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.









