

Product Code: VPMB751BK

## **Technical Specification**



Description: 13A Ingot Double Pole Switched Fused Connection Unit







### **General Information**

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Matt Black Insert Colour Black

Gasket Colour Black

Front Plate: Stainless Steel

Switch & Fuse Drawer Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Gasket: Nylon

Anti Microbial Certified

Operating Voltage (AC) 250

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

**Termination Type** Screw Terminal Size (mm)

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Switched Yes

Double Pole Switch Twin Earth Terminals Product Marking Fused

Minimum Back Box Depth (mm) 25 Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-4, BS 1362

# Materials

Internal Busbars: Formed Pressed Brass

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Insert & Housing: Urea

Earth Strap: Mild Steel

Terminals: Brass

Terminal Torque Value (Nm) 2

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Supplied with Matt Black plate fixing screws.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









