











Discharge - Single Ended Hot Restrike CSR12000/SE/HR/UV-C

97272

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance -Available with UV blocking.

Application areas



Film and Broadcast









97272

Product data

Product Code	97272
Bulb Shape	Tubular
Bulb Finish	Clear
Light Center Length [mm]	255
Net weight per piece [g]	1200
Gross weight per piece [g]	2600
Operating position	U - Universal
Brand	General Electric (GE)
Cap/Base	G38

Performance data

Weighted energy consumption [kWh/1000h]	13200
Energy efficiency class (EEC)	A+
Nominal chromaticity coordinate X	0.3
Nominal chromaticity coordinate Y	0.3
Nominal correlated colour temperature (CCT) [K]]	6000
Nominal lumens [lm]	1150000
Colour Rendering Index (CRI) [Ra]	90

Electrical data

Dimming Capability	Yes
Nominal power [W]	12000
Nominal lamp voltage [V]	160



Discharge - Single Ended Hot Restrike CSR12000/SE/HR/UV-C

97272

Logistic data

DUN Code	10043168972724
EAN Code	0043168972727
Pack Quantity	4
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	8 UK
Layer quantity UK	8
Pallet quantity UK (PC)	8
Outer case size	540 x 540 x 610 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination