

**ACCENTPLUS SCOOP ADJUSTABLE DOWNLIGHT 13.5W 1620LM 120LM/W  
3000K CRI90 92MM CUTOUT 36 BEAM WHITE 36VDC 350MA - NO DRIVER**

ILDL92SC001



Integral Scoop downlights are a commercial solution for washing walls or displays with high quality CRI 90 real colour lighting. They feature fully rotatable bezels and a 38° downward tilt which brings the fitting well below the ceiling line allowing precise beam control, lighting areas that would not be possible with conventional downlights. The range includes versions with no driver, which can be paired to our standard DALI, push dim, 0-10V combination dimmable drivers (see suggested products for driver options).

**Details**

<b>Barcode:</b>	5055788275367
<b>Quick Order Code:</b>	102251
<b>Category:</b>	Downlights
<b>Range Name:</b>	AccentPlus Scoop
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Commercial indoor
<b>Features:</b>	Adjustable
<b>Fixed/Tiltable:</b>	Tiltable
<b>Warranty (Years):</b>	5

**Physical Data**

<b>Product Depth (mm):</b>	62
<b>Product Weight (g):</b>	280
<b>Overall diameter (mm):</b>	100
<b>Construction:</b>	Aluminium
<b>Cut Out Diameter (mm):</b>	92
<b>Bulb or Luminaire Shape:</b>	Round
<b>Luminaire Fixing:</b>	Recess mounted
<b>Placement / Application:</b>	Indoor, General Lighting
<b>Spot Type:</b>	COB

**Electrical Data**

<b>Power Consumption (W) :</b>	13.5
<b>Power Factor:</b>	0.9
<b>Amperage (mA):</b>	350
<b>Driver Included:</b>	No

<b>Electric Current:</b>	DC
<b>EN:</b>	IEC 62031
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	1620
<b>Luminous efficacy (lm/W):</b>	120
<b>Colour Temperature:</b>	3000K - Warm White
<b>Beam Angle:</b>	36
<b>Colour Rendering Index (CRI):</b>	90
<b>Integrated Light Source:</b>	Yes
<b>Lifetime (hours):</b>	50000

## Environment

<b>EN:</b>	IEC 62031
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Back/Recessed side):</b>	IP20
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

## Packaging

<b>Barcode:</b>	5055788275367
<b>Single box qty:</b>	1
<b>Package Weight (g):</b>	310
<b>Package Length (mm):</b>	125
<b>Package Width (mm):</b>	120
<b>Package Depth (mm):</b>	90
<b>Qty per Inner Carton :</b>	10
<b>Inner Carton Length (mm):</b>	575
<b>Inner Carton Width (mm):</b>	230
<b>Inner Carton Depth (mm):</b>	90
<b>Qty per Outer Carton:</b>	36
<b>Outer Carton Length (mm):</b>	480
<b>Outer Carton Width (mm):</b>	360
<b>Outer Carton Depth (mm):</b>	290
<b>Qty per euro pallet:</b>	864