

Ei3030



Multi-Sensor Fire & CO Alarm



- Containing our proven Thermistor Heat Sensor, Optical Sensor and Electrochemical CO Sensor to provide the ultimate response, working independently and together
- Offering visual indicators that trigger according to which alarm is activated
- Built-in intelligent dust compensation technology eliminating the risk of nuisance alarms from contamination
- Built-in AudioLINK+ technology
- Mains powered with 10-year rechargeable lithium cell back-up



Description

The Ei3030 is a mains powered Multi-Sensor Fire and CO Alarm with 10 Year Rechargeable Lithium Back-up. It contains built-in AudioLINK+ data extraction technology and is upgradeable to SmartLINK wireless interconnection using an Ei3000MRF module

Technical

Sensor Type	Optical, Thermistor - Class A1 & Electrochemical CO	Indicators	Green - Power / Red - Alarm / Yellow - Fault
Supply Voltage (V)	230	Voltage Type	AC
Battery Type	Lithium rechargeable	Power Consumption (W)	0.25
Technologies	AudioLINK+		

Dimensions & Weights

Depth (mm)	66	Height (mm)	150
Width (mm)	150	Product weight (kg)	0.347
Packaged weight (kg)	0.399		

Approvals & Warranty

Certification/Approvals	EN 14604:2005+AC 2008, BS 5446-2:2003, EN 50291-1:2018	Warranty	5 year warranty
EAN Number	5099383010466		

Environmental

Humidity Range (%)	15-95	Temperature Range (°C)	-10 to 40
---------------------------	-------	-------------------------------	-----------