

# PL LAMP HOLDERS

## NPL9-18 PENDANT FOR 2 & 4 PIN 9-18W PL LAMPS

PL pendant with 6-pin socket for 2 and 4 pin 9-18W PL lamps.



## NPL13 PENDANT FOR 4 PIN 13W PL LAMPS ONLY

PL pendant with 4-pin socket for 13W lamps only.



## NPL18 PENDANT FOR 4 PIN 18W PL LAMPS ONLY

PL pendant with 4-pin socket for 18W lamps only.



## NPLB9-18 BATTEN HOLDER FOR 2 & 4 PIN 9-18W PL LAMPS

PL battenholder with 6-pin socket for 2 and 4 pin 9-18W PL lamps.



# LOW VOLTAGE TRANSFORMER

## NCG/XFMR/60 TRANSFORMER 12V 60VA DIMMABLE

- 60VA
- Dimmable with leading edge (triac) dimmers
- Auto-reset short-circuit protection
- Thermal cut-out - non resettable



# PHOTO-CELLS

## NPECK PHOTO-ELECTRIC CELL KIT

- 230-240V, 50/60Hz
- 5A switching capacity
- 20 lux on, 80 lux off
- IP65



## NPECR PHOTO-ELECTRIC CELL REMOTE

- 230-240V, 50/60Hz
- 5A switching capacity
- 20 lux on, 80 lux off
- IP65 when fitted
- Dimensions: 52 x 20.5 x 20.5. 17mm clearance hole for installation
- Pre-wired with 300mm, 3 cores



## NPECH PHOTO-ELECTRIC CELL HEAD

- 230-240V, 50/60Hz
- 5A switching capacity
- 20 lux on, 80 lux off
- IP65 when fitted
- NEMA male connector base



## NPECH PHOTO-ELECTRIC CELL HEAD

- 230-240V, 50/60Hz
- 5A switching capacity
- 20 lux on, 80 lux off
- IP65 when fitted
- NEMA male connector base

