




Indy K3 125-165-200W

Wattage Switchable Symmetrical Floodlight

Features

IK Rating	IK07
IP Rating	IP65
CSP Switchable	Single CCT
Tilttable	180°
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
CRI	CRI>80
SDCM	SDCM5
Emergency Option	No

Installation information

Install Connector Type	Flying lead
Inrush Current	IFLB1N: 30.3A 0.22ms IFLB2N: 53A 0.22ms IFLB3N: 30.3A 0.22ms
Construction Material	Die-cast aluminium (body) stainless steel 304 (bracket)
Weight	IFLB1N_: 2.5kg IFLB2N_: 4.5kg IFLB3N_: 7.1kg
Ambient Temperature Range	-40°C - 40°C
SELV	No
UK Building Regulations	Part P
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
IFLB2N40	Black	165	4000K	120°	25000	156	8747
IFLB2N40	Black	200	4000K	120°	27500	152	9621
IFLB2N30	Black	165	3000K	120°	24500	148	8572
IFLB2N30	Black	200	3000K	120°	27000	135	9446

Wiring information

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel

Accessories

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately
----------	----------------------------	-----------------



01604 495 151
collingwoodlighting.com

collingwoodled
 /collingwoodlighting
 collingwoodlighting

Guarantee

5 years (product), 2 years (on-site)

Features & benefits

High efficacy up to 152lm/W
Wattage switchable between 125-200W
Suitable for use in coastal applications
Quick and easy installation with angle stamped brackets
Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications
Compatible with the PCELLKIT dusk to dawn sensor
6kV Surge Protection
Asymmetrical floodlights also available in K2 product range
Suitable for mounted upside down as an uplight

Light source energy efficiency:



Beam angle: 120°

