



The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.







General Information

Ambient	-20°C to 40°C	
Temperature		
Range (°C)		
IP Rating	IP20	
Nominal	15,000 h	
Lifetime (h)		
Protection	Class II	
Rating		
Installation	Internal	
Area		





FC4.2D-SES27 07630

Filament Candle 4.2W Dimmable SES (E14) 2700K Clear

- Linear LED filament provides a traditional appearance
- Save energy up to 90% compared with an incandescent filament lamp
- Even light distribution



Technical Summary		
Product Code	FC4.2D-SES27	
Input Voltage Supply	220-240Vac 50/60Hz	
Default Power	4.2 W	
Power Factor	0.4	
Default CCT	2,700 K	
SDCM of CCT	<6	
CRI	80	
Dimmable	Y	
Flicker	<10%	
Lumens Output Maximum	470 lm	
Maximum Efficiency	112 lm/W	
L80B10 Lifetime (h) @Ta 25 °C	15,000 h	
Nominal Lifetime (h)	15,000 h	
Weight	20g	
Dimensions (L x W x D) (mm)	98x⊘35	











KosnicLightingUK

Tel: 01635 523 713 Email: sales@kosnic.com

Kosnic.com



Dimmable Clear Candle Kosnic



07630 FC4.2D-SES27

Overview

The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.







General Information

Ambient	-20°C to 40°C
Temperature	
Range (°C)	
IP Rating	IP20
Nominal	15,000 h
Lifetime (h)	
Protection	Class II
Rating	
Installation	Internal
Area	





Kosnic Lighting





KosnicLightingUK

Tel: 01635 523 713 Email: sales@kosnic.com

Kosnic.com



