

# Vintage Filament ST64

07843 VST4.2-ES25

## Vintage Filament ST64 4.2W ES (E27) 2500K gold antique coating

- Special coating with a gold finish gives an antique appearance
- Linear LED filament provides a traditional appearance
- Creates a warm and cosy living space
- Even light distribution
- Save energy up to 90% compared with an incandescent filament lamp



### Overview

The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.



### General Information

|                                |               |
|--------------------------------|---------------|
| Ambient Temperature Range (°C) | -20°C to 40°C |
| IP Rating                      | IP20          |
| Protection Rating              | Class II      |
| Installation Area              | Internal      |
| L80B10 Lifetime (h) @Ta 25 °C  | 15,000 h      |

### Compliance

|     |                                                                                                     |
|-----|-----------------------------------------------------------------------------------------------------|
| LVD | EN 62031:2020, EN 62471:2008, EN 62493:2015+A1:2022, EN 62560:2012+A11:2019                         |
| EMC | EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023 |

### Technical Summary

|                                    |                    |
|------------------------------------|--------------------|
| Product Code                       | VST4.2-ES25        |
| Input Voltage Supply               | 220-240Vac 50/60Hz |
| Inrush Current (peak/duration) (A) | 3.6A/1440us        |
| Default Power                      | 4.2 W              |
| Power Factor                       | 0.4                |
| Default CCT                        | 2,500 K            |
| SDCM of CCT                        | <6                 |
| CRI                                | 80                 |
| Dimmable                           | N                  |
| Flicker                            | <10%               |
| Lumens Output Maximum              | 450 lm             |
| Maximum Efficiency                 | 112 lm/W           |
| L70B50 Lifetime (h) @Ta 25 °C      | 15,000 h           |
| L80B10 Lifetime (h) @Ta 25 °C      | 15,000 h           |
| L90B10 Lifetime (h) @Ta 25 °C      | 5,000 h            |
| Nominal Lifetime (h)               | 15,000 h           |
| Blue Light Hazard                  | RG1                |
| Weight                             | 0.041Kg            |
| Dimensions (L x W x D) (mm)        | 140xØ64            |
| LS Energy Efficiency Class         | F                  |

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)



[Kosnic.com](http://Kosnic.com)



07843 VST4.2-ES25

## Overview

The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.



## General Information

|                                |               |
|--------------------------------|---------------|
| Ambient Temperature Range (°C) | -20°C to 40°C |
| IP Rating                      | IP20          |
| Nominal Lifetime (h)           | 15,000 h      |
| Protection Rating              | Class II      |
| Installation Area              | Internal      |

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)

