

# Ceiling Pull Unit

Part No. **NC807C**



## Overview

Can be used to generate a standard call on an 800 Series Conventional Call System.

Typically wired as a slave to an 800 Series Call Point or Reset Point so that its calls can be cancelled.

Supplied with 3m of red nylon pull cord and two red open-sided triangular bangles for ease of use by the infirm.

Red confidence LED and diffuser emits a bright red glow over a wide area to reassure the user that a call has been made.

Surface mountable.

Base fits 16mm conduit and BESA centres.

## Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and the number / type of field devices connected to the system.
Indicators	Red reassurance LED/diffuser (active in Alarm).
Controls	Red pull cord c/w two red open-sided triangular bangles.
Onboard Sounder	No.
Product dimensions (mm)	93mm diameter x 27mm deep. Designed for ceiling mounting only. Base fits 16mm conduit and BESA centres.
Construction & finish	Plastic.
IP Rating	IP21.
Weight	55g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom