

Linear

Grafham Plug & Play Linear Internal 2W Emergency Pack

Grafham Plug & Play Linear Internal 2W Emergency pack



General Data

Mounting options	Internal
Input Electrical Connection	Plug & Play
General Application	Commercial Industrial Educational
Operating Temperature Range °C	0 - +60
Warranty (Years)	5

Electrical Data

Wattage (W)	2
Total power consumption (W)	2
Mains voltage (V)	220 - 240
Electrical protection	Class II
Driver Output Current (mA)	<40
Control Gear Type CC or CV	Constant Current
Driver Brand	Lumineux
Nominal Frequency (Hz)	50 60

430962

Technical Specification

Emergency Data

Battery Type	LiFeP04
Battery Capacity (mAh)	3200
Battery Warranty (Years)	5
Recharge Time (Hours)	24 Hours
Emergency Type	E-SEL3 - Non Maintained Maintained
Test Procedure	Manual Self Test
Emergency Duration (Hours)	3

Physical Data

Housing Colour	White
IP Rating	20
Nominal Product Length (mm)	170
Nominal Product Width (mm)	54
Nominal Product Height (mm)	32
Weight (kg)	0.23

Standards and Approvals

Manufactured In Accordance To	EN 60598-1 EN 60598-2
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate of Conformity	Available on Request
Accredited Members	LIA, ISO9001

