

Luminaires | Downlights

Slim-FitCS™ 6W IP44 Colour Switchable Low Profile Downlight

AU-PL06CS



Photometrics

Wattage	6
Lumens	550
Lm/W	92
Beam Angle	120
Colour Temperature	3000 / 4000 / 6500
Ra	650
SDCM	5
UGR19	NO

Product Features

Brand	Aurora
IP Rating	IP44
IK Rating	IK06
L70 Hours	L80 50,000
Lifetime Class	L80
SKU Type	Non Dim
Dimmable	NO
Warranty	5 Years

Onsite Warranty	3 Years
Country of Origin	CN

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.9
Surge Protection (kV)	0.5
Inrush Current (A)	8
Protection Class	CLASS TWO
Fire Protection	NO
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	NO

Physical Attributes

Height (mm)	22
Overall Diameter (mm)	120
Lamp Base	LED
Cutout Diameter Min. (mm)	106
Cutout Diameter Max. (mm)	108
Mount Options	RECESSED
Finish Colour	White