

Luminaires | Downlights

Slim-FitCS™ 12W IP44 Colour Switchable Low Profile Downlight

AU-PL12CS



Photometrics

Wattage	12
Lumens	1320
Lm/W	110
Beam Angle	120
Colour Temperature	3000 / 4000 / 6500
Ra	650
UGR19	NO

Product Features

Brand	Aurora
IP Rating	IP44
IK Rating	IK06
L70 Hours	L80 50,000
Lifetime Class	L80
SKU Type	Non Dim
Dimmable	NO
0-10V Dimming?	NO
DALI Dimming?	NO

1-10V Dimming?	NO
DALI-2 Dimming?	NO
DMX Dimming?	NO
DSI Dimming?	NO
Warranty	5
Onsite Warranty	3
Country of Origin	CN

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.9
Surge Protection (kV)	0.5
Inrush Current (A)	8
Protection Class	CLASS TWO
Fire Protection	NO
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	NO

Physical Attributes

Height (mm)	22
Overall Diameter (mm)	170
Lamp Base	LED
Cutout Diameter Min. (mm)	157
Cutout Diameter Max. (mm)	157
Mount Options	RECESSED
Finish Colour	White