

## Luminaires | Downlights

# Slim-FitCS™ 24W IP44 Colour Switchable Low Profile Downlight

AU-PL24CS



## Photometrics

|                           |                    |
|---------------------------|--------------------|
| <b>Wattage</b>            | 24                 |
| <b>Lumens</b>             | 2620               |
| <b>Lm/W</b>               | 110                |
| <b>Beam Angle</b>         | 120                |
| <b>Colour Temperature</b> | 3000 / 4000 / 6500 |
| <b>Ra</b>                 | 650                |
| <b>UGR19</b>              | NO                 |

## Product Features

|                        |            |
|------------------------|------------|
| <b>Brand</b>           | Aurora     |
| <b>IP Rating</b>       | IP44       |
| <b>IK Rating</b>       | IK06       |
| <b>L70 Hours</b>       | L80 50,000 |
| <b>Lifetime Class</b>  | L80        |
| <b>SKU Type</b>        | Non Dim    |
| <b>Dimmable</b>        | NO         |
| <b>Warranty</b>        | 5          |
| <b>Onsite Warranty</b> | 3          |

Country of Origin CN

## Electrical Specification

Input Voltage (Min) 220

Input Voltage (Max) 240

Input Voltage Type AC

Power Factor 0.9

Surge Protection (kV) 0.5

Inrush Current (A) 22

Protection Class CLASS TWO

Fire Protection NO

Frequency (Min) Hz. 50

Frequency (Max) Hz. 60

Operating Temp. (Max) °C 40

Glow Wire Test (°C) NO

## Physical Attributes

Height (mm) 22

Overall Diameter (mm) 300

Lamp Base LED

Cutout Diameter Min. (mm) 280

Cutout Diameter Max. (mm) 280

Finish Colour White