

**ACCENTPLUS SCOOP ADJUSTABLE DOWNLIGHT 125MM CUTOUT 2420LM  
22W 3000K 110LM/W CRI90 36 BEAM WHITE 36VDC 600MA - NO DRIVER**

ILDL125SC003



The AccentPlus Scoop Adjustable Downlight is a versatile and high-performance lighting solution, ideal for accentuating walls or displays with exceptional colour accuracy. Delivering warm white 3000K illumination with a CRI of 90 this downlight provides true-to-life colour rendering for commercial and architectural applications. Designed with precision in mind, the fitting features a fully rotatable bezel and a 36° beam angle, complemented by a 38° downward tilt. This innovative design allows the downlight to extend below the ceiling line, enabling precise beam placement and illumination of areas that standard downlights cannot reach. This model comes without a driver, offering flexibility for pairing with standard DALI, push dim, or 0-10V combination dimmable drivers to suit your project's requirements. For compatible driver options, refer to the suggested products list.

**Details**

<b>Barcode:</b>	5055788302988
<b>Quick Order Code:</b>	785060
<b>Category:</b>	Downlights
<b>Range Name:</b>	AccentPlus Scoop
<b>Product Type:</b>	Downlight
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Commercial indoor, Residential indoor
<b>Features:</b>	Adjustable
<b>Fixed/Tiltable:</b>	Tiltable
<b>Warranty (Years):</b>	5

**Physical Data**

<b>Product Depth (mm):</b>	96
<b>Product Weight (g):</b>	800
<b>Optic:</b>	Clear Refractor
<b>Material:</b>	Aluminium alloy
<b>Overall diameter (mm):</b>	160
<b>Construction:</b>	Aluminium
<b>Cut Out Diameter (mm):</b>	125
<b>Bulb or Luminaire Shape:</b>	Round
<b>Luminaire Fixing:</b>	Recess mounted
<b>Placement / Application:</b>	Indoor, General Lighting
<b>Spot Type:</b>	COB

## Electrical Data

Power Consumption (W) :	22
Power Factor:	0.9
Voltage Range (v):	220-240
Amperage (mA):	600
Driver Included:	No
Electric Current:	AC
EN:	EN-60598
LVD Certified:	Yes

## Light Data

Luminous Flux in Lumens (lm):	2420
Luminous efficacy (lm/W):	110
Correlated Colour Temperature (CCT) (K):	3000
Colour Temperature:	3000K - Warm White
Colour Temperature Name:	Warm White
Beam Angle:	36
Colour Rendering Index (CRI):	90
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	Chip on board (COB)
Lifetime (hours):	50000
Switching Cycles:	100000
Useful Lumens (lm):	2500

## Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Back/Recessed side):	IP20
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

## Packaging

Barcode:	5055788302988
Package Weight (g):	900
Package Length (mm):	180
Package Width (mm):	180
Package Depth (mm):	116