





General Information

Dimensions (mm)	1500 (L) x 63 (W) x 80 (D)
Materials	Base: Powder Coated Aluminium; Opaque Diffuser: Polycarbonate
Bezel Colour	White (RAL9003)
Product Weight (Kg)	1.26
Ingress Protection	IP20
Impact Rating (IK)	06
Flammability Rating	TP(a)
Mounting	Ceiling or Wall
Warranty (Years)	5

Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50)
Safety Class	I
Circuit Wattage (W)	30/37/45/52
LED Wattage Options (W)	30/37/45/52
Input Current (mA)	250
Inrush Current	60A (5ms)
Power Factor	0.9
Efficiency (%)	90
Driver Information	Integrated
Operating Temperature (°C)	-20 to +45
Maximum Critical Temperature (°C)	80
Input Terminations	Push-fit Terminals
Start-up Time	<0.5s

Luminaire Output

Colour Temperature (K)	3000	4000	6000
LED Wattage	30		
Typical Luminous Flux (lm)	3300	3600	3300
Efficacy (lm/W)	110	120	110
LED Wattage	37		
Typical Luminous Flux (lm)	4070	4440	4070
Efficacy (lm/W)	110	120	110
LED Wattage	45		
Typical Luminous Flux (lm)	4950	5400	4950
Efficacy (lm/W)	110	120	110
LED Wattage	52		
Typical Luminous Flux (lm)	5720	6240	5720
Efficacy (lm/W)	110	120	110
Beam Angle (°)	120		
Colour Rendering Index (CRI)	80		
Flicker Free	Yes		
LED Lifetime (L70) (Hours)	50000		

Dimming Information

Dimmable	No
----------	----

Compatible Accessories

OSUSS15 - 2 x Suspension Cable for Linear Luminaires



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com



Catalogue



Section



DoC



Installation

