Product Code: GM1020PW   Luckinslive   437662419

Description: 10A 3 Pole Fan Isolation Switch Module

General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)
Colour	Polar White
Insert Colour	Polar White

Materials	Body & Insert: Nylon		Switch: Urea
	Insert Cover: Stainless Steel		Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated		Contacts: Silver "on-lay" Copper / Brass

Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	10		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5		
Triple Pole Switch	Yes		
Product Marking	On, Off Fan Isolator		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards   BS EN 60669-2-4, BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches both the Deco white range and Metal Clad range.

CLIP-ON MODULES   SCREW-IN MODULES

UK Patent: GB 2578427

Catalogue   Range   DoC   Installation

CLICK OR SCAN