

Product Code: GM1030PW

Luckinslive 437662671

Description: 10A 3 Pole Fan Isolation Keyswitch Module



**General Information**

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)	
Colour	Polar White	
Insert Colour	Polar White	
Materials	Body & Insert: Nylon	Switch: Nylon
	Insert Cover: Stainless Steel	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	10	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm <sup>2</sup> )	4 x 1.5 or 2 x 2.5	
Triple Pole Switch	Yes	
Keyswitch	Yes	
Product Marking	On, Off Isolator	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

**Standards** BS EN 60669-2-4, BS EN 60669-1

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches both the Deco white range and Metal Clad range.

UK Patent: GB 2578427



Scolmore House, Mariner, Lichfield Road Industrial Estate,  
Tamworth, Staffordshire, B79 7UL United Kingdom  
T: +44 (0)1827 63454 | F: +44 (0)1827 63362  
E: sales@scolmore.com | W: scolmore.com



CLICK OR SCAN

Catalogue



Range



DoC



Installation



CLICK OR SCAN