

T8 CCT

08736 T8CCT22

T8 CCT 12W/22W Glass LED T8 tube 3000/4000/6500K

- High efficiency up to 150lm/W
- Save energy by up to 65%
- Switchable wattage and CCT (3000/4000/6500K)
- Flicker free

Overview

The T8 CCT is a highly energy efficient glass T8 tube that can help you save energy by up to 65%. And with its long life you can keep making savings for years to come. Plus, this version can completely adapt to your needs with its switchable wattage and CCT capabilities.



IP20

General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IP Rating	IP20
Protection Rating	Class II

Compliance

LVD	EN 62493:2015+A1:2022, EN 62776:2015
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	RoHS, Ecodesign 2009/125/EC

Technical Summary

Product Code	T8CCT22
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	10A/190us
Settable Wattages	12W, 22W
Power Factor	0.5
Settable Colour Temperatures	3000K, 4000K, 6500K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	<10%
Lumens Output Maximum	3,100 lm
L70B50 Lifetime (h) @Ta 25 °C	25,000 h
Nominal Lifetime (h)	25,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG0
Weight	0.270Kg
Dimensions (L x W x D) (mm)	1514xØ28
Beam Angle - Lumi (°)	180
LS Energy Efficiency Class	D

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



T8 CCT

08736 T8CCT22


Overview

The T8 CCT is a highly energy efficient glass T8 tube that can help you save energy by up to 65%. And with its long life you can keep making savings for years to come. Plus, this version can completely adapt to your needs with its switchable wattage and CCT capabilities.



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IP Rating	IP20
Nominal Lifetime (h)	25,000 h
Protection Rating	Class II



Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

