

Product Code: OB41GLV400

Luckinslive 437546263

Description: OB41 Galvanising Spray 400ml Aerosol

**Benefits**

- Fast-drying film
- High adhesive strength
- Can be lacquered over
- Heat-resistant up to +200°C
- Has the same colour as newly galvanized metals

OB41 Galvanising Spray is a mixture of aluminium and zinc and offers heatresistant corrosion protection for many materials. It adheres very well to non-ferrous metals and iron. Galvanising Spray can be used for regalvanizing and repairing damaged spots on galvanized parts as well as on welding and cutting points in steelgirder construction. Galvanising Spray takes on the task of corrosion protection and acts as an optical colour compensator due to its similar colour to newly galvanized metals.

Colour Galvanised**Application**

Galvanised Spray is applied in industry, trade and other areas where galvanized metals are processed or damaged. Its main applications are in the field of air-conditioning and ventilation, heating systems, pipe construction and powerhouses

Directions Of Use

Ideal temperature +16°C to +25°C. Degrease metals and grind them smoothly. Shake the spray vigorously for about three minutes after the clearly audible striking of the metal ball. Apply the spray crosswise from a distance of approx. 25-30cm. The surface is dry after 5-8 minutes, fast to handling after 15-20 minutes and completely dry after approx. 24 hours

Additional Information

Application Temperature	+16°C to +25°C
Base	Synthetic resin
Curing Time	24 hours
Density	0.733
Frost Resistance During Transportation	Down to -15°C
Solids	0.115
Temperature Resistance	-30°C to +200°C
Tack Free Time	20-30 min

These values are typical values

Shelf Life

24 months when stored as recommended in original unopened packaging

Health & Safety

We recommend that you view the Safety Data Sheet (SDS) for further information on the product before use.

