



15 Way High Integrity 100A Switch 2x 100A 30mA RCCB Single Mod Type II SPD

Technical Features

Installation, mounting

|             |               |
|-------------|---------------|
| Mounting on | Wall mounting |
|-------------|---------------|

Architecture

|                 |   |
|-----------------|---|
| Number of poles | 2 |
|-----------------|---|

Functions

|                            |     |
|----------------------------|-----|
| Has protection main switch | Yes |
| Overvoltage protection     | Yes |

Installation, mounting

|                            |    |
|----------------------------|----|
| Suitable for outdoor usage | No |
|----------------------------|----|

Configuration

|                                            |   |
|--------------------------------------------|---|
| Number of arc fault detection devices AFDD | 0 |
|--------------------------------------------|---|

Capacity

|                   |    |
|-------------------|----|
| Number of modules | 15 |
|-------------------|----|

Electric current

|               |       |
|---------------|-------|
| Rated current | 100 A |
|---------------|-------|

Weight

|        |        |
|--------|--------|
| Weight | 5.9 kg |
|--------|--------|

Dimensions

|        |          |
|--------|----------|
| Depth  | 102.5 mm |
| Height | 204 mm   |
| Width  | 472 mm   |

Cover, door

|                           |    |
|---------------------------|----|
| Interlockable             | No |
| Door/cover is transparent | No |

Materials

|          |       |
|----------|-------|
| RAL code | 9010  |
| Colour   | White |
| Material | Steel |

Connection

|                             |   |
|-----------------------------|---|
| Number of conduit inlets    | 0 |
| Number of accessible phases | 1 |

Scope of delivery

|                                                |   |
|------------------------------------------------|---|
| Number of earth leakage circuit breaker type A | 0 |
| Number of RCCB in enclosure                    | 2 |

Equipment

|                       |    |
|-----------------------|----|
| Number of rows        | 1  |
| With energy meter     | No |
| Number of rails       | 1  |
| Extension possible    | No |
| With bell transformer | No |
| With socket outlet    | No |

Safety

|                                         |       |
|-----------------------------------------|-------|
| Impact resistance IK                    | IK05  |
| Ingress Protection (IP) class           | IP2XC |
| Number of earth leakage switches 30 mA  | 2     |
| Number of earth leakage switches 300 mA | 0     |

**Compatibility**

|                                              |    |
|----------------------------------------------|----|
| Cooker group suitable as power current group | No |
|----------------------------------------------|----|

**Sustainability**

|              |     |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|