



Topline Evo



Part of the Battens and Weatherproofs product category

Model Topline EVO CCT Multi Wattage 1200mm
Code ATLEVO4
Application Ancillary, Commercial, Education, Healthcare, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	18W - 32W
Operating Temp	-10°C - 40°C
Lumens Delivered	2500lm - 4300lm (4000K)
lm/W	140lm/W
CCT	3000/4000/5700K
UGR	24
Beam Angle	105/140

MATERIAL INFORMATION

Main Material	Steel
Diffuser Material	Polycarbonate
Product Weight without Packaging	1.42 kg
Colour / Finish	White
Height	70 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.8
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- High performance, multi-wattage LED CCT batten suitable for industrial and multi-purpose applications
- Selectable CCT between 3000K, 4000K and 5700K
- High efficiency up to 140 lm/W
- Power selectable; offering high and low output option in each length
- Excellent light uniformity through high transmittance polycarbonate diffuser





Topline Evo



Part of the Battens and Weatherproofs product category

Model Topline EVO CCT Multi Wattage 1200mm
Code ATLEVO4
Application Ancillary, Commercial, Education, Healthcare, Industrial, Retail

